Options

Options are factory installed. Order as suffix of the fixture catalogue number.

	Description	Bandit	GeoFloods	Powerhouse	FX Series	Recflood	FloodPak	FTM / FTL
FS	Fusing (120,277 or 347V only)	–	–	–		–		–
AM	Automatic quartz socket and relay (Lamp not supplied)		–				–	–
PCB	Button Photocontrol for 120, 277 or 347V		–		–		–	
SP	Mirror-Specular, long-throw reflector			–				
TLR	Twist lock photocontrol receptacle	–		–				–
HL	Hi-Lo Dimming				–			
SL	Stabilux Lamp Support (Not available for Type D or Type E)				–			
F1	Fusing (120, 277, 347V only)				–			
LV	Internal glare control louvres					–		
LQ	Auxiliary Quartz				–			
EX	Extender box, allows size of lower wattage units to match higher wattage units		–					
GS	External Glare Shield					–		
LB	Less Ballast					–		

Accessories

Accessories are field installed. Order as separate line item.

	Description	Dynolite	Miniray	Bandit	GeoFloods	Powerhouse	Paraflood	FX Series	Recflood	FloodPak
SL552	Polycarbonate shield, vandal resistant	–	–							
RPP	Rocket Perma Post for time-savings with ground mounting	–	–							
75	4" round junction box	–	–							
2	Single hole box cover	–	–							
7	2" Slipfitter	–	–							
BT552	Polycarbonate Shield, vandal resitant			–						
BT10	Universal Slipfitter (2") for 2 3/8" O.D. tenon (Used with BTY model)			–						
FPSAA	Adjustable arm 1/2" NPT for FPS & FPM									–
FPLAA	Adjustable arm 2" tenon for FPL									–
FPSPMA	Pole Mount arm FPS/FPM (converts FPS/FPM Floodpak to pole mount)									–
FPLPMA	Pole Mount arm FPL (converts FPL Floodpak to pole mount)									–
FPSVS	Vandal Shield for FPS									–
FPMVS	Vandal Shield for FPM									–
FPLVS	Vandal Shield for FPL									–
FPSRPA	Round Pole Adapter for FPS & FPM (for use with FPSPMA)									–
FPLRPA	Round Pole Adapter for FPL (for use with FPLPMA)									–
GRWG	Wireguard protects against breakage in vandal prone applications				–					
GFVL	Polycarbonate lens guards against breakage in vandal prone applications			–						
GFGS	Single piece hood top mounted to control glare when unit is tilted back over 25°			–						
PH522	Polycarbonate shield - up to 400W					–				
PH1152	Polycarbonate shield - 1000W					–				
PH551	Glare shield - up to 400 W					–				
PH1151	Glare shield - 1000W					–				
PARA3	Universal Mounting Arm to convert pipe mount units into universal mounting applications. (Comes c/w 3' cabtire)					–				
PR6666	Reflector Kit (Four segment reflector kit snaps into place without tools to provide NEMA 6x6 Distribution						–			
PR552	Lexan Shield for protection from vandalism (For 400W max.)						–			
SK-40-FX, SK-100-FX	Top Shield (400 watt), Top Shield (1000 watt)							–		
AL-40-FX, AL-100-FX	Polycarbonate lens (400 watt), Polycarbonate lens (1000 watt)							–		
BD-40-FX, BD-100-FX	Barndoors (400 watt), Barndoors (1000 watt)							–		
IGL-40-FX, IGL-10-FX	Internal Louver (400 watt), Internal Louver (1000 watt)							–		
WG-40-FX, WG-10-FX	Wireguard (400 watt), Wireguard (1000 watt)							–		
SMT	Surface Mounting Tenon W/ flat plate							–		
SM18	Stanchion Mount Bracket							–		
VMA-ISW-FX4, VMA-ISW-FX10	Wall Bracket (400 watt), Wall Bracket (1000 watt)							–		
VMAS15	Vertical Arm for straight square poles							–		
PTA-H2180-FX(4OR10)	Pole Top Adapter with horizontal tenons (400 or 1000 watt)							–		
CMC-FX	Ceiling Mount (Indoors Only)							–		
PTA-(*)-16.5	Pole Adapter bracket with vertical tenons (400 or 1000 watt) * 2180 - 2 luminaires @180°, 2090 - 2 luminaires @ 90°, 3090 - 3 luminaires @ 90°, 4090 - 4 luminaires @ 90°							–		
P105A	Adjustable Photocontrol, 120V (not suitable for use with FPSAA)									–
P105M	Adjustable Photocontrol, 208-240-277V (not suitable for use with FPSAA)									–
P150A	Adjustable photocontrol, 120V	–	–							–
P150B	Adjustable Photocontrol, 208-277V	–	–							–
P150W	Adjustable Photocontrol, 347V	–	–							–
LB	Less Ballast								–	
GS	External Glare Shield								–	