



LytePro 32 LED Wall Sconce

LPW32-79DGY

LED, 6913 lumens, 71W, 700mA, 4000K, 347-480V, Textured Dark Gray - 98 lm/W

The Lytepro 32 Series Architectural Wall Sconce from KEENE incorporates modern styling, high performance, and energy efficient LEDs. Featuring Philips LedGine platform for future proof designs that enhance upgrades and simplify replacements. Ideal LED solution to replace 150 watt and 175 watt HID sources with up to 60% energy savings.

Product data

General Information		Approval and Application	
Lamp Source Code	LED	Safety Listing	ETL
Colour Temperature	4000k	DesignLights Consortium Qualified Product List	DesignLights Consortium Qualified Product List
CRI	70		
Photometric Distribution Type	Type III		
Mounting	Wall		
B.U.G. Rating	B2U0G2		
Awards	DLC QPL		
Operating and Electrical		Initial Performance (IEC Compliant)	
Voltages	347 V	Luminaire Lumens	6900
Luminaire Input Watts	71	Efficacy	98 lm/W
Mechanical and Housing		Application Conditions	
Shape	Oval	Max Ambient Temp	+40 °C
		Min Ambient Temp	-40 °C
		Product Data	
		Order product name	LPW32-79DGY
		EAN/UPC - Product	190096011407

LytePro 32 LED Wall Sconce

Order code	912400531039
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912400531039
Net Weight (Piece)	0.200 kg

Catalog Number	LPW32-79DGY
Catalog Number Description	LED, 6913 lumens, 71W, 700mA, 4000K, 347-480V, Textured Dark Gray

