


Copper Clad Groundrods and Connectors




CATALOGUE #	SIZE	WT./LBS./C	CATALOGUE #	SIZE	WT./LBS./C
1205CC	1/2" x 5"	260	3406CC	3/4" x 6"	720
1206CC	1/2" x 6"	305	3408CC	3/4" x 8"	960
1208CC	1/2" x 8"	410	3409CC	3/4" x 9"	1080
1210CC	1/2" x 10"	520	3410CC	3/4" x 10"	1200
5805CC	5/8" x 5"	400	1008CC	1" x 8"	1700
5806CC	5/8" x 6"	580	1010CC	1" x 10"	2130
5808CC	5/8" x 8"	640			
5809CC	5/8" x 9"	740			
5810CC	5/8" x 10"	800			



Sectional Copper Clad Rods

CATALOGUE #	SIZE	WT./LBS./C	CATALOGUE #	SIZE	WT./LBS./C
1208SC	1/2" x 8"	410	3408SC	3/4" x 8"	960
1210SC	1/2" x 10"	510	3410SC	3/4" x 10"	1200
5808SC	5/8" x 8"	640	1010SC	1" x 10"	2130
5810SC	5/8" x 10"	800			




Couplings

Driving Studs

CATALOGUE #	SIZE	WT./LBS./C	CATALOGUE #	SIZE	WT./LBS./C
12SC	1/2"	15	12DS	1/2"	15
58SC	5/8"	26	58DS	5/8"	23
34SC	3/4"	42	34DS	3/4"	35
10SC	1"	85	10DS	1"	81

Sectional copper clad rods are threaded at top and bottom. Two or more rods may be coupled together to make up the desired length. Threaded couplings are made of bronze. Driving studs are made of high strength carbon steel and are used to prevent damage to top-end threads or couplings. 1 stud required every 2 rods.



POLELINE
&
GROUNDING