





## Connection kits for XL-Trace, IceStop and RaySol self-regulating heating cables

The Raychem FTC heat shrinkable connection kits are used with XL-Trace, IceStop and RaySol self-regulating heating cables.

The FTC connection kits are designed to provide low cost power connection and low profile splice and tee kits.

The FTC power connection kits can be used for circuit breakers rated up to 40 A.

### Powered Connection Kits

Catalog number	Part number	Description
<b>FTC-P</b> 	111711-000	Power connection kit with end seal: The FTC-P power connection and end seal kit is for use with XL-Trace, RaySol and IceStop heating cables. Materials for one power connection and end seal is included in the kit.
<b>FTC-XC</b> 	368979-000	Power connection kit with end seal: The FTC-XC power connection and end seal kit is for use with XL-Trace and RaySol heating cables that are run through conduit to a junction box. Materials for one power connection and end seal is included in the kit.
<b>FTC-HST</b> 	354169-000	Splice or Tee kit: The FTC-HST splice or tee kit is for use with XL-Trace, RaySol and IceStop heating cables. Material for two splice or tees included in each kit.
<b>FTC-PSK</b> 	P00000927	Pipe stand and power connection kit: The FTC-PSK pipe stand and power connection kit is for use with XL-Trace heating cables. The stand is designed specifically for the DigiTrace ECW-GF electronic controllers and is compatible with other junction boxes that have 1 inch NPT entries, threaded or non-threaded. Materials for one power connection and end seal is included in the kit.





**Specifications**

Rated voltage	120–277 V
Maximum circuit breaker size	40 A
Maximum exposure temperature	150°F (65°C)
Minimum installation temperature	0°F (–18°C)
Enclosure rating	NEMA 4X

**Applicable Products**

XL-Trace	5/8XL1-CR/CT and 5/8/12XL2-CR/CT
IceStop	GM-1XT, GM-1X, GM-2XT and GM-2X
RaySol	RaySol-1 and RaySol-2

**Approvals**

	<p>718K Pipe Heating Cable or 877Z De-Icing and Snow Melting Equipment or 9J8 6 Radiant Heating Cable</p>		<p>Certified with IceStop and RaySol heating cables</p>
	<p>With XL-Trace and IceStop heating cables</p> <p>Hazardous locations: Class I, Div 2. Groups A, B, C, D GM-1XT and GM-2XT only</p>		<p>For XL-Trace heating cables</p>

**Design and Installation**

For proper design and installation of a FTC connection kit, use the appropriate product design guide and the installation instructions included with the connection kit.

**Ground-Fault Protection**

To minimize the danger of fire from sustained electrical arcing if the heating cable is damaged or improperly installed, and to comply with the requirements of Tyco Thermal Controls, agency certifications, and national electrical codes, ground-fault equipment protection must be used on each heating cable branch circuit. Arcing may not be stopped by conventional circuit protection.

**Worldwide Headquarters  
Tyco Thermal Controls**

7433 Harwin Drive  
Houston, TX 77036  
USA  
Tel: 800-545-6258  
Tel: 650-216-1526  
Fax: 800-527-5703  
Fax: 650-474-7711  
info@tycothermal.com  
[www.tycothermal.com](http://www.tycothermal.com)

**Canada  
Tyco Thermal Controls**

250 West St.  
Trenton, Ontario K8V 5S2  
Canada  
Tel: 800-545-6258  
Fax: 800-527-5703  
Tel: 613-392-6571  
Fax: 613-392-3999

**Europe, Middle East, Africa  
Tyco Thermal Controls**

Romeinse straat 14  
3001 Leuven  
België / Belgique  
Tel: +32 16 213 511  
Fax: +32 16 213 603

**Latin America  
Tyco Thermal Controls**

Al. Araguaia, 2044 – Sala.1101,  
Bloco B  
Edifício CEA – Alphaville  
Barueri – Sao Paulo – Brasil  
06455-000  
Tel: +55 11 2588 1400  
Fax: +55 11 2588 1410

**Asia Pacific  
Tyco Thermal Controls**

20F, Innovation Building,  
1009 Yi Shan Rd,  
Shanghai 200233, P.R.China  
Tel: +86 21 2412 1688  
Fax: +86 21 5426 2937 / 5426 3167

Tyco, Alliance Integrated Systems, AMC, AutoMatrix, AutoSol, BTV, CapaciSense, Chemelex, DHSX, DigiTrace, DigiTrace logo, DigiTrace Supervisor, Duoterm, ElectroMelt, EM2XR, FHSM, FHSC, FlexFit, FlexiClic, Flowguard, FreezeTrace, FreezGard, Frostex, Frostex Plus, Frostguard, FroStop, FSE, Gardian, HAK, Handvise, HBTv, HCCL, HotCap, HQTV, HTPG, HTPi, HWAT, HXTV, IceStop, Interlock, JBM, JBS, K-Flex, K-Flex logo, KHE, KHH, KHL, KHP, KTV, Labsafe, LBTv, LHC, LHFV, LHRV, Metabond, Mini WinterGard, Miser WinterGard, MoniTrace, Multi-plus, NGC, PetroTrace, PLI, PolyMatrix, Pyro CiC, PyroFLX, Pyromaster, Pyropak, Pyrosil, PyroSizer, Pyrotenax, Pyrotenax Designer, Pyrotenax logo, QTVR, QuickNet, QuickNet logo, QuickStat, QuickTerm, RayClic, RaySol, RayStat, Retro WinterGard, RHS, RHSC, RHSM, RMM2, SBF, SBV, SC, SHC, Sheathmaster, ShowerGuard, SLBTV, Smart Heat for Comfort and Safety, SnoCalc, SnoCalc logo, STS, System 500, System 1850, System 1850-SE, System 2000, System 2200, T2, T2 logo, T2Blue, T2QuickNet, T2Red, T2Reflecta, TankCalc Plus, TempBus, Thermoheat, ThermoLimit, Thermo-Line, Total Care in Heat-tracing, Touch, Trac-Loc, Trac Calc, TraceCalc Net, TraceCalc Net logo, TraceCalc Pro logo, TraceGuard 277, TraceMaster, Tracer, Tracer logo, TRACERLYNX, TRACERLYNX logo, TraceStat, TraceTek, TraceTek logo, TruckPak, VLBTv, VLKTV, VPL, We manage the heat you need, WinterGard, WinterGard logo, WinterGard Plus, WinterGard Wet, XL-ERATE, XL-ERATE logo, XL-Trace, XTV and Zero EMI are registered and/or unregistered trademarks of Tyco Thermal Controls LLC or its affiliates.

All other trademarks are the property of their respective owners.

**tyco**  
Thermal Controls

**Important:** All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their particular application. Tyco Thermal Controls makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. Tyco Thermal Controls' only obligations are those in the Tyco Thermal Controls Standard Terms and Conditions of Sale for this product, and in no case will Tyco Thermal Controls or its distributors be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of the product. Specifications are subject to change without notice. In addition, Tyco Thermal Controls reserves the right to make changes—without notification to Buyer—to processing or materials that do not affect compliance with any applicable specification.