

SECTION 5

Pipe Straps, Pipe Clamps and Hangers

Conduit and Cable Clamps

6H Series
Conduit and Pipe Hanger



6H Series



6H-B Series
with Bolt and Hex Nut



6H-TB
Threaded Series



6H-T
Threaded Series

Features

- Accommodates 1/2" through 4" EMT or rigid conduit
- Can be used for either vertical or horizontal installation
- 6HTB Series have a built-in nut so there are fewer parts to handle or drop
- Installs easily with a screwdriver

Cat. No.	Conduit Size		Wt./C lb
	Rigid	EMT	
6H0	3/8" - 1/2"	1/2"	5
6H0-B	3/8" - 1/2"	1/2"	7
6H0-T	3/8" - 1/2"	1/2"	5
6H0-TB	3/8" - 1/2"	1/2"	6
6H1	3/4"	3/4"	6
6H1-B	3/4"	3/4"	7
6H1-T	3/4"	3/4"	6
6H1-TB	3/4"	3/4"	7
6H2	1"	1"	7
6H2-B	1"	1"	9
6H2-1/2	-	1-1/4"	8
6H2-1/2-B	-	1-1/4"	10
6H3-SC	1-1/4"	1-1/2"	8
6H3-B	1-1/4"	1-1/2"	10
6H3-TB	1-1/4"	1-1/2"	10
6H4	1-1/2"	-	17
6H4-B	1-1/2"	-	19
6H4-TB	1-1/2"	-	19
6H5	2"	2"	24
6H5-B	2"	2"	26
6H5-TB	2"	2"	26
6H6	2-1/2"	2-1/2"	28
6H6-B	2-1/2"	2-1/2"	30
6H7	3"	3"	36
6H7-B	3"	3"	38
6H8	3-1/2"	3-1/2"	39
6H8-B	3-1/2"	3-1/2"	41
6H9	4"	4"	44
6H9-B	4"	4"	47




Standard Finish - Electrogalvanized (no suffix)
Available in Stainless Steel 304 (SS)

Cable Tie Mounting Bases
For Framing Channel



Cat. No.	Channel Size	Maximum Tie Width Accom.	Unit Qty.	Std. Pkg.
TC5363X	1-1/2 & 1-5/8	.301	50	250

INSTALLATION



- Installs with a push and twist
- Designed for indoor or outdoor use
- Smooth design protects cable insulation
- Takes range of cable diameters

When fastening wire bundles, cables, or hoses to framing channels, you can cut costs considerably by using this mounting base. It is made of smooth, weather-resistant nylon and designed to protect cable insulation and hoses from the wear or damage that can occur with metal clamps. The mounting base may be used for both indoor or outdoor applications. It installs in the framing channel with a simple push and twist. It requires no screws, nuts or tools. The mounting base fits all 1-1/2" and 1-5/8" channels regardless of channel depth. Ty-Rap® and Ty-Fast® to be ordered separately.