

UL 1077 T&B Catalog Number:

S203-C2

UPC Number: 66201917694

Status: Active

Description:

3 pole, 2 amps rated at 480Y/277 VAC, UL 1077 series miniature circuit breaker with thermal-magnetic trip device, C trip curve, and 6kA interrupt current rating

current rating	
Features	
	High performance MCB provides compact supple-
	mentary, energy limiting, circuit protection
	Fast breaking time
	Bus connection system
	Finger safe terminals
	Suitable for reverse feed
Application	
	For use as a supplemental protection device
	Designed for use in cable protection applications,
	such as in control circuits and lighting applications
	For use with resistive loads
General	
Mounting Method	DIN Rail
Trip Type	Thermal-magnetic
Number of Poles	3
Series	S200-C
Terminal Type	Screw
Approvals	
UL Class	UL 1077
Dimension Information	
H x W x D (inches)	3.35 x 2.07 x 2.98
H x W x D (mm)	88 x 52.5 x 69
Specifications	
Rated Current (Amps)	2
Rated Voltage AC	480Y/277
Interrupt Rating (kA)	6
Trip Curve	С
Packaging	
Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	0.92 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com