Technical Information Bulletin - LED



ORDERING INFORMATION

Order code: 63610

Description: LED/P20/7.6W/30K/25/ELUME

UPC: 069549636101

Case quantity: 20



PERFORMANCE DATA

Shape: PAR₂₀ Wattage (W): 7.6 E26 Lamp voltage (VAC): 120 Colour temperature (K)**: 3 000 Average life (L70 hours): 40 000 Initial lumens (lm)*: 534 Initial lumens per watt (lm/W): 70 CBCP: 1 179 CRI: 80 Beam angle: 25 Power factor:

-20 °C / -4 °F to 45 °C / 113 °F Operating temperature range:

*Initial lumens range: +/- 5 % **Typical colour temperature range: +/- 5 %



















For a complete list of ENERGY STAR qualified products, please visit www.standardpro.com.

COMPATIBLE DIMMER LIST

Legrand: HCL453P

Cooper: DAL06P, SAL06P, SLC03P

Leviton: DSM10-1LZ

Lutron: CTCL-153P, DVELV-300P, SELV-300P, NTELV-600

CAUTIONS

• Risk of electric shock, for use in dry locations only.
• Suitable for use in open luminaires.
• For complete dimmer compatibility and warranty information visit www.standardpro.com
• Operating temperature: -20 °C/-4 °F to 45 °C/113 °F
NOTES: This device complies with Part 15 of the FCC rules and has been tested and found to comply with the limits for a Class B digital device. This product may cause interference with other devices. If interference occurs, change the location of the product. Any changes or modifications not expressively approved by the manufacturer could void the user's authority to operate the equipment. This RFLD device complies with Canadian ICES-003. LED lamps must be stored, operated under suitable environmental conditions and in accordance with, but not limited to, the latest National Electrical Code, cETLus, cULus, CSA and ANSI specifications.

