


Technical Information Bulletin - LED

E-Lume™

ORDERING INFORMATION

Order code: 63612
Description: LED/P30S/9W/30K/25/ELUME
UPC: 069549636125
Case quantity: 20



PERFORMANCE DATA

Shape:	PAR30SN
Wattage (W):	9
Base:	E26
Lamp voltage (VAC):	120
Colour temperature (K)**:	3 000
Average life (L70 hours):	40 000
Initial lumens (lm)*:	800
Initial lumens per watt (lm/W):	89
CBCP:	2 910
CRI:	80
Beam angle:	25
Power factor:	0.9
Operating temperature range:	-20 °C / -4 °F to 45 °C / 113 °F

*Initial lumens range: +/- 5 %

**Typical colour temperature range: +/- 5 %



For a complete list of ENERGY STAR qualified products, please visit www.standardpro.com.

COMPATIBLE DIMMER LIST

Legrand: HCL453P
Cooper: DAL06P, SAL06P, SLC03P
Leviton: DSM10-1LZ
Lutron: CTCL-153P, DVELV-300P, SELV-300P, NTELV-600

CAUTIONS

- Risk of electric shock, for use in dry locations only.
- Suitable for use in open luminaires.
- For complete dimmer compatibility and warranty information visit www.standardpro.com
- Operating temperature: -20 °C/-4 °F to 45 °C/113 °F

NOTES: This device complies with Part 15 of the FCC rules and has been tested and found to comply with the limits for a Class B digital device. This product may cause interference with other devices. If interference occurs, change the location of the product. Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment. This RFLD device complies with Canadian ICES-003. LED lamps must be stored, operated under suitable environmental conditions and in accordance with, but not limited to, the latest National Electrical Code, cETLus, cULus, CSA and ANSI specifications.

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

December 3, 2015

STANDARD®