



IC200DTX200



IC200DTX450



IC200DTX850



IC200DTX650

DataPanels Operator Interfaces

GE VersaMax DataPanels are ideal for a broad range of applications ranging from simple timer/counter/register access to full text message display with numeric keypad. All VersaMax DataPanels are preprogrammed to connect quickly to a VersaMax Micro or Nano PLC without user configuration.

	IC200DTX200	IC200DTX450	IC200DTX650	IC200DTX850
Product Name	Operator Interface for changing timer/counter/register values. 2x16 character LCD backlight display and 6 operation keys. No stored messaging, PLC stores messages. Requires IC200CBL550 cable or equivalent. Operates on 5 VDC @ 100 mA from Micro or Nano.	Operator Interface with up to 200 stored messages. 2x16 character LCD backlight display and 6 function keys. Requires IC200CBL555 or equivalent. Operates on external 24 VDC @ 40 mA.	Operator Interface with up to 200 stored messages. 4x16 character LCD backlight display and 8 function keys. Requires IC200CBL555 cable or equivalent. Operates on external 24 VDC @ 80 mA.	Operator Interface with up to 200 stored messages. 4x20 character LCD backlight display, 8 function keys and numeric keypad. Requires IC200CBL555 cable or equivalent. Operates on external 24 VDC @ 50 mA.
Lifecycle Status	Active	Active	Active	Active
Characters Per Line	16	16	16	20
Function Keys	0	6	8	8
Numeric Keypad	0	0	0	Yes
Memory Size (Number of Messages)	Messages stored in PLC	200 stored in operator interface	200 stored in operator interface	200 stored in operator interface
DataPanel Dimensions (WxHxD) mm	108x60x27	108x60x45	96x96x44	182x101x37
Number of Lines	2	2	4	4
Display Type	LCD Display with Backlight	LCD Display with Backlight	LCD Display with Backlight	LCD Display with Backlight
Operating Temperature	0°C to +50°C	0°C to +50°C	0°C to +50°C	0°C to +50°C
NEMA Rating	NEMA 4	NEMA 4	NEMA 4	NEMA 4
Programming Software	None required	DataDesigner (IC752DDZ000)	DataDesigner (IC752DDZ000)	DataDesigner (IC752DDZ000)