

Discrete Expansion Units



The VersaMax Micro’s modular design provides you with remarkable flexibility in a compact control. The versatile Micro PLC can support up to four Expansion Units of any mix of discrete or analog.

	IC200UEX009	IC200UEX010	IC200UEX215	IC200UEX213	IC200UEX214
Product Name	14 point (8) 120 VAC In, (6) Relay Out (2 outputs at 10 amp and 4 outputs at 2 amp), 120/240 VAC Powered	14 point (8) 120 VAC In, (6) 120 VAC Out, 120/240 VAC Powered	28 point (16) 12 VDC In, (12) 12 VDC Out, 12 VDC Powered	28 point (16) 12 VDC In, (12) Relay Out, 12 VDC Powered	28 point (16) 24 VDC In, (12) 24 VDC Out, 24 VDC Powered
Lifecycle Status	Active	Active	Active	Active	Active
Micro Type Restrictions	N/A	N/A	N/A	N/A	N/A
Number of Discrete Inputs/Outputs	8 In / 6 Out	8 In / 6 Out	16 In / 12 Out	16 In / 12 Out	16 In / 12 Out
Power Voltage	120/240 VAC	120/240 VAC	12 VDC	12 VDC	24 VDC
Input Power Supply Rating	11 VA	11 VA	8 Watts	8 Watts	5 Watts
24 VDC User Power for Sensors	200 mA	200 mA	200 mA	200 mA	200 mA
Input Device Voltage	120 VAC	120 VAC	12 VDC	12 VDC	24 VDC
Output Control Voltage	Relay Out (2 at 10 Amps and 4 at 2 Amps)	120 VAC	12 VDC	Relay Out	24 VDC
Relay Maximum Resistive Load Rating	2 Amps at 24 VDC and 240 VAC; 10 Amp at 24 VDC and 240 VAC	N/A	N/A	2 Amps at 24 VDC and 240 VAC	N/A
Dimensions (WxHxD) mm	95x90x76	95x90x76	150x90x76	150x90x76	150x90x76