



### Remote Base Power Supplies

The RX3i power supply modules simply snap in just like I/O, and they work with any model CPU. Each version provides auto-ranging so there is no need to set jumpers for different incoming power levels, and they are current limiting so a direct short will shut the power supply down to avoid damage to the hardware. RX3i power supplies are tied into the performance of the CPU for simplex, fail-safe, and fault tolerance. Advanced diagnostics and built-in smart switch fusing are among the other performance and safety features.

	IC694PWR321	IC694PWR330	IC694PWR331	IC693PWR332
<b>Product Name</b>	Power Supply, 120/240 VAC, 125 VDC	Power Supply, 120/240 VAC, 125 VDC	Power Supply, 24 VDC	Power Supply, 12 VDC
<b>Lifecycle Status</b>	Active	Active	Active	Active
<b>Module Type</b>	Expansion Power Supply	Expansion Power Supply	Expansion Power Supply	Expansion Power Supply
<b>Backplane Support</b>	Remote Bases Only	Remote Bases Only	Remote Bases Only	Remote Bases Only
<b>Power Source</b>	100-240 VAC or 125 VDC	100-240 VAC or 125 VDC	24 VDC	12 VDC
<b>High Capacity</b>	No	Yes	Yes	Yes
<b>Output Source</b>	30 watts total; 15 watts 5 VDC; 15 watts 24 VDC relay; 20 watts 24 VDC isolated	30 watts total; 30 watts 5 V; 15 watts 24 V relay; 20 watts 24 V isolated	30 watts total; 30 watts 5 V; 15 watts 24 V relay; 20 watts 24 V isolated	30 watts total; 30 watts 5 V; 15 watts 24 V relay; 20 watts 24 V isolated
<b>Cable Length to Redundant Power Supply Adapter</b>	N/A	N/A	N/A	N/A
<b>Redundant Power Supply Adapter Rack Compatibility</b>	N/A	N/A	N/A	N/A
<b>24 VDC Output Current Capacity</b>	0.8 A	0.8 A	0.8 A	0.8 A