



## Power Modules

The RSTi provides various power modules to reduce wiring and simplify installation. Modules that support Smart Module ID will require one of the addresses on the bus.

The ST-7241 and ST-7641 enable multiple voltages to be supported on the RSTi bus such as 120 VAC. All modules to the right of the module will be based on the supply voltage of the ST-7x41.

The ST-7111 and ST-7511 boost the 5 VDC on the backplane bus when module power requirement is exceeded. The ST-7x11 supplies 1.0 Amps of 5 VDC to the modules to the right of the ST-7x11.

	ST-7111	ST-7511	ST-7241	ST-7641
<b>Product Name</b>	<b>Bus Expansion Power Supply (Input 24 VDC, Output 1.0 Amp/5 VDC)</b>	<b>Bus Expansion Smart Power Supply (Input 24 VDC, Output 1.0 Amp/5 VDC)</b>	<b>Power Distribution (5 VDC, 24 VDC, 48 VDC, 110 VAC, 220 VAC)</b>	<b>Power Distribution Smart Module (5 VDC, 24 VDC, 48 VDC, 110 VAC, 220 VAC)</b>
<b>Lifecycle Status</b>	Active	Active	Active	Active
<b>Module Type</b>	Power Modules	Power Modules	Power Modules	Power Modules
<b>Smart Module (Uses Module ID)</b>	No	Yes	No	Yes
<b>Load Current per Point</b>	Max. 10 Amps	Max. 10 Amps	Max. 10 Amps	Max. 10 Amps
<b>LEDs</b>	Yes	1 Green/Red LED, Module Status	No	1 Green/Red LED, Module Status
<b>Diagnostic Supported</b>	No	No	No	No
<b>Connector Type</b>	Spring Clamp Terminal Block	Spring Clamp Terminal Block	Spring Clamp Terminal Block	Spring Clamp Terminal Block
<b>Internal Power Used (5 VDC loading)</b>	1.0 Amp 5 VDC booster	Max. 14 mA @ 24 VDC	None	Max. 18 mA @ 5 VDC
<b>Dimensions (H x W x D) in mm</b>	99 x 12 x 70	99 x 12 x 70	99 x 12 x 70	99 x 12 x 70