

ULT COPPER C CRIMPS

- Manufactured from high strength copper alloy.
- Clearly marked with wire size and die index.
- UL 486A/B Listed for 600 Volts.
- If proper high voltage spacings and insulation techniques are used, may be used for high voltage applications up to 35KV.
- Range taking.
- Provides easy identification and tooling recommendation.
- For Copper Conductor only.
- UL File E6207



Item ID	Conductor Range Main	Conductor Range Tap	Length	Die Index Number	Standard Package Quantity	NAED/UPC Number
ULT-4-Z	4 STR-6 SOL	6 STR-6 SOL	0.7500	BG OR 5/8	100	78366993075
ULT-5-Z	4 STR-6 SOL	4 STR-4 SOL	0.7500	BG OR 5/8	100	78366993077
ULT-6-Z	2 STR-2 SOL	4 STR-8 SOL	0.8750	C	100	78366993079
ULT-7-Z	2 STR-2 SOL	2 STR-2 SOL	0.8750	C	100	78366993081
ULT-12-Z	4/0 STR-3/0 STR	4/0 STR-3/0 STR	1.1250	F OR D3	25	78366993083

[RETURN](#)

IlSCO is Registered in the U.S. Patent and Trademark Office.
[Privacy Statement](#)