

Wieland Electric



Datasheet

Art.No. 81.020.4100.0

Relay module E-TIMER-S-250V6A

Flare-Timer-S, multi-function timer relay, time range 0,1s..300s, DC 24 V



| Art.No. | 81.020.4100.0 |
|------------|---------------|
| EAN | 4015573438798 |
| Order unit | 10 pieces |

Approvals



Technical data

General

| Connection type | Tension clamp connection |
|--|--------------------------|
| Plug-in socket | No |
| Remote operation possible | No |
| Only for remote control | No |
| Function flashing, starting with pause, fixed time | Yes |
| Function flashing, starting with pulse, fixed time | Yes |
| Clock function, starting with pause, variable | No |
| Clock function, starting with pulse, variable | No |
| Number of relay outputs, undelayed, change-over contacts | 0 |
| Relay outputs, delayed/undelayed selectable | No |
| Number of relay outputs, undelayed, normally closed | 0 |
| Number of relay outputs, undelayed, normally open | 0 |
| Number of relay outputs, delayed, change-over contacts | 0 |
| Number of relay outputs, delayed, normally open | 0 |
| Number of relay outputs, delayed, change-over contacts | 0 |
| Semiconductor output | No |
| Function delay-on energization | Yes |
| Function floating contact on energization | Yes |
| Function star-delta | No |
| Function delay on de-energization | Yes |
| Function floating contact on de-energization | No |
| Function pulse shaping | No |





Technical data

| Type of excitation | |
|-------------------------|---------|
| With auxiliary voltage | Yes |
| Min. nominal voltage DC | 24 V |
| Min. adjustable time | 0.1 sec |
| Max. adjustable time | 300 sec |

Dimensions

| Depth | 70 mm |
|--------|--------|
| Width | 6.2 mm |
| Height | 89 mm |