
B6IC-100

6" Universal 100W IC Housing **Double Wall**

LAMP WATTAGE: (1) MAX. 75W R/PAR40/PAR38, 75W R/PAR30, 60W A19, 65W BR30



DESIGNED FOR 2" X 8" JOIST CONSTRUCTION









ITEM SELECTOR: (Please check the boxes below for the option desired)


Catalog Number:	
Project Name:	Туре:
Note:	elite

DESCRIPTION

For new construction. Thermally protected, IC rated specification grade recessed housing. Accommodates up to 100W R40, par38, 75W PAR30, R30 lamps, 60W A19 lamps and 65W BR30 lamps. Furnished with preinstalled adjustable bar hangers. Junction box is provided with four ½" KOs. one ¾" KO and four Romex knockouts with strain relief.

SPECIFICATION

- A. OUTER HOUSING Die formed aluminum construction for maximum heat dissipating air chamber on top of the housing. Junction box could be accessed from inside and outside housing.
- B. INNER HOUSING Die-formed all aluminum construction for maximum heat dissipation and rust protection. Adjusts vertically in plaster frame to accommodate 1/2" to 1-3/8" ceiling.
- C. SOCKET Medium base screw shell porcelain socket preinstalled on adjustable mounting bracket is designed to allow usage of different lamp types, as well as proper and consistent lamp positioning.
- D. BAR HANGERS Preinstalled bar hangers allow housing to be positioned and locked at any point within a 24" joist span. They can be positioned on either the long or short axis of the housing and can be shortened for 12" joists. They contain a double-headed real nail for 20° downward angle for better contact, and the 90° pivoting mounting plate makes installation fast and accurate. Bar hangers can fit onto T-Bar spline with additional slots and holes for special mounting methods if necessary.
- E. JUNCTION BOX ETL listed for through-branch circuit wiring and has four ½" KOs, one ¾" KO and four Romex knockouts with true pry-out slots and strain clamps.
- F. THERMAL PROTECTION Standard thermal protection device guards against improper installation, overlamping and misuse of insulation material.



BEAM DIA. MEASURED AT 50% OF NADIR F.C.

FEATURES

- Thermally Protected IC housing.
- · Adjustable socket bracket.
- · Wire through junction box.
- · Preinstalled adjustable bar hanger.
- Dependable, favorable design and effortless installation.
- 7-1/2" height allows use in 2" x 8" joist construction.
- Special screw on the frame locks bar hangers in place which prevents the housing from any movement once installed.
- Preinstalled socket cap provides electrical contact protection against dust, paint and over spray.

OPTIONS AIR-SHUT

- · Gasket to prevent air flow from heated or air conditioned spaces.
- . Meets all national air flow requirements.

ETL AND C-ETL LISTED

- For Damp location
- For Feed-through wiring
- For Direct contact with insulation


ТҮРЕ	AIR-SHUT	OPTION	TRIM TYPE						BAFFLE	REFLECTOR	TRIM/RING	GLASS	
B6IC-100	□ AT	☐ (W) With quick connects	□ B630	□ B608	□ B601	□ B637	□ B615	□ B622	□ B689	□ w	□ CL	□ WH	□ Green
			□ B640	□ B602	□ B601L	□ B643	□ B633	□ B623	□ B680	□Р	□ RG	□ BK	☐ Yellow
			□ B620	□ B609	□ B605	□ B658	□ B634	□ B625		□ SN	□ W	□ SN	□ Pink
			□ B631	□ B619	□ B605L	□ B659	□ B649	□ B624		□ CP	□ MB	□ CP	□ Brown
			□ B632	□ B646	□ B606	□ B675	☐ AF633	□ B681		□ BZ	□ BZ	□ CH	☐ Navy Blue
			☐ AF637	□ B616	□ B606L	□ B676	□ B225	□ B687			□ СР	□ PB	☐ Orange
			☐ AF631	□ B663	□ B635	□ B612	□ B653	□ B682			□ SN	□ BZ	□ Blue
			☐ AF639	□ B664	□ B636	□ B645	□ B651	□ B693			□ SHZ		☐ White
			☐ AF640	□ B673	□ B641	□ B648	□ B611	□ B694					□ Red
			□ B610	□ B674	□ B642	□ B652	□ B647	□ B688					
			□ B607	□ B683	□ B656	□ B603	□ B644	□ B685					
			□ B627	□ B684	□ B657	□ B604	□ B650	□ B696					
											DEEL FOTOD	TDIM/DIMO	

Specifications:

B6IC-100

AIR-SHUT BAFFLE OPTION TRIM TYPE GLASS

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory,



Sample of Catalog Number: B6IC-100-AT-W-B630-W-WH

Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977

Incandescent Trims

(LAMP WATTAGE: (1) MAX. 75W R/PAR40/PAR38, 75W R/PAR30, 60W A19, 65W BR30)


Catalog Number: Project Name: Type: Note: eitë lighting

B630CP-CP **METAL STEPPED BAFFLE R30/PAR30**



BAFFLE FINISH:

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7




B640SN-SN **METAL STEPPED BAFFLE R40/PAR38**



BAFFLE FINISH:

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7



B620-ORANGE GLASS TRIM



GLASS FINISH: GREEN, YELLOW PINK, BROWN, NAVY BLUE, ORANGE.




B631P-WH R30 PREMIUM PHENOLIC BAFFLE / METAL RING



BAFFLE FINISH:

TRIM/RING FINISH: PB. B7




B632W-WH R40 PREMIUM PHENOLIC BAFFLE / METAL RING



BAFFLE FINISH:

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



AF637W-WH **SELF FLANGE AIR-SHUT BAFFLE**



COMBINATIONS: W-WH, P-WH, P-BK, SN-SN, CP-CP, BZ-BZ



AF631W-WH **SELF FLANGE AIR-SHUT BAFFLE**



COMBINATIONS: W-WH, P-WH, P-BK, SN-SN, CP-CP, BZ-BZ



AF639W-WH **SELF FLANGE AIR-SHUT BAFFLE**



AF640W-WH **DEEP SELF FLANGE AIR-SHUT BAFFLE**



B610P-RG-WH CONE REFLECTOR/BAFFLE TRIM



BAFFLE FINISH:

REFLECTOR FINISH: CL. RG

TRIM/RING FINISH: WH, BK, SN, CP, CH,



B607CP-WH **REFLECTOR R/PAR30**



REFLECTOR FINISH: CL, RG, W, MB, CP, SN, BZ, SHZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7




B627RG-WH **REFLECTOR R40/PAR38**



REFLECTOR FINISH: CL, RG, W, MB, CP, SN, BZ, SHZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B608CL-WH **CONE REFLECTOR A19**



REFLECTOR FINISH: CL, RG, W, MB, CP, SN, BZ, SHZ


TRIM/RING FINISH: WH, BK, SN, CP, CH,



B602SN EYEBALL



TRIM/RING FINISH: WH, BK, SN, CP, CH,



B609W-WH **REGRESSED EYEBALL WITH BAFFLE**



BAFFLE FINISH: W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7

EYEBALL FINISH: WH, BK, SN, CP, CH, PB, BZ

B619RG-PB REGRESSED EYEBALL WITH REFLECTOR



REFLECTOR FINISH: CL, RG, W, MB, CP, SN

TRIM/RING FINISH: WH, BK, SN, CP, CH,



EYEBALL FINISH: WH, BK, SN, CP, CH, PB, BZ



Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice.

REV: MAXILUME-SPEC-05-26-2011

Incandescent Trims

(LAMP WATTAGE: (1) MAX. 75W R/PAR40/PAR38, 75W R/PAR30, 60W A19, 65W BR30)

Catalog Number: Project Name: Type:

elite LIGHTING

B646P-WH **EYEBALL WITH BAFFLE**



BAFFLE FINISH:

TRIM/RING FINISH:




B616W-WH PAR20 REGRESSED EYEBALL W/ BAFFLE



BAFFLE FINISH:

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7




Note:

EYEBALL FINISH: WH, BK, SN, CP, CH, PB, BZ

B663PB PAR30 GIMBAL RING




TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7



B664CP PAR38 GIMBAL RING



TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ




B673P-WH PAR30 BAFFLE W/ GIMBAL RING



BAFFLE FINISH: W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ




B674W-WH PAR38 BAFFLE W/ GIMBAL RING



BAFFLE FINISH: W, P, SN, CP, BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ




B683CL-WH PAR30 REFLECTOR W/ GIMBAL RING



REFLECTOR FINISH: CL, RG, W, MB, CP, SN

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ




B684RG-WH PAR38 REFLECTOR W/ GIMBAL RING



REFLECTOR FINISH: CL, RG, W, MB, CP, SN


TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ



B601CP METAL ALBALITE LENS



LENS: ALBALITE TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ




B601L PLASTIC ALBALITE LENS



LENS: ALBALITE

TRIM/RING FINISH: WHITE PLASTIC




B605PB

METAL FRESNEL LENS



LENS: FRESNEL

TRIM/RING FINISH: WH, BK, SN, CP, CH




B605L

PLASTIC FRESNEL LENS



LENS: FRESNEI

TRIM/RING FINISH: WHITE PLASTIC



B606CP METAL DROP OPAL LENS



LENS: DROP OPAL

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B606L

PLASTIC DROP OPAL LENS



LENS: DROP OPAL

TRIM/RING FINISH:



B635P-WH **BAFFLE W/ ALBALITE LENS**



BAFFLE FINISH: W. P. SN. CP. BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH,



7-1/4"


B636W-WH

BAFFLE W/ FRESNEL LENS



BAFFLE FINISH:

TRIM/RING FINISH: WH, BK, SN, CP, CH,





Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice.

REV: MAXILUME-SPEC-05-26-2011

Incandescent Trims

(LAMP WATTAGE: (1) MAX. 75W R/PAR40/PAR38, 75W R/PAR30, 60W A19, 65W BR30)

Catalog Number: Project Name: Type: Note:


e të lighting

B657CL-WH

B641RG-WH **REFLECTOR W/ ALBALITE LENS**

















BAFFLE W/ FROSTED DOME SHOWER LENS





REFLECTOR W/ FROSTED DOME SHOWER LENS




REFLECTOR FINISH: CL, RG, W, MB, CP, SN, SHZ



REFLECTOR FINISH: CL, RG, W, MB, CP, SN. SH7

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ

B643RG-WH




BAFFLE FINISH:

B656W-WH

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. B7

B658CL-WH



REFLECTOR FINISH: CL, RG, W, MB, CP, SN, SHZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ

B659CL-WH



B637W-WH **BAFFLE W/ DROP OPAL LENS**







REFLECTOR W/ DROP OPAL LENS





REFLECTOR W/ PRISMATIC LENS






REFLECTOR W/ FROSTED LENS



BAFFLE FINISH: W, P, SN, CP, BZ





REFLECTOR FINISH: CL, RG, W, MB, CP, SN. SHZ

TRIM/RING FINISH: WH. BK. SN. CP. CH. PB, BZ

B676W-WH



REFLECTOR FINISH: CL, RG, W, MB, CP, SN, SHZ

TRIM/RING FINISH: WH. BK. SN. CP. CH. PB, BZ


B612WH



REFLECTOR FINISH:

CL, RG, W, MB, CP, SN. SHZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B675W-WH BAFFLE W/ PRISMATIC LENS







BAFFLE W/ FROSTED LENS





SMOOTH FROST DOME SHOWER LENS








BAFFLE FINISH: W, P, SN, CP, BZ





BAFFLE FINISH:

W, P, SN, CP, BZ TRIM/RING FINISH: WH, BK, SN, CP, CH,



LENS: FROSTFD

TRIM/RING FINISH: WH, BK, SN, CP, CH



B645WH


LENS:

DESIGNER POINT SHOWER LENS





FROSTED/CLEAR TRIM/RING FINISH: WH, BK, SN, CP, CH,



B648WH DESIGNER CONE SHOWER LENS







B652WH **SMOOTH FROST SHOWER LENS**





B603CP R/PAR30 OPEN TRIM





B604PB R40/PAR38 OPEN TRIM



TRIM/RING FINISH: WH, BK, SN, CP, CH,




LENS: FROSTED

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ











Specifications and Dimensions

6" Incandescent Trims

(LAMP WATTAGE: (1) MAX. 75W R/PAR40/PAR38, 75W R/PAR30, 60W A19, 65W BR30)

Catalog Number:

Project Name:

Type:

Note:


B615WH DESIGNER PINHOLE



B633WH R/PAR30 SPLAY TRIM



TRIM/RING FINISH:



B634WH R40/PAR38 SPLAY TRIM



TRIM/RING FINISH:



B649RG-WH PAR20 REFLECTOR




REFLECTOR FINISH: CL, RG, W, MB, CP, SN

TRIM/RING FINISH: WH, BK




AF633CH R/PAR30 OPEN TRIM



B225WH OPEN TRIM STEPPED BAFFLE



BAFFLE FINISH: W, P TRIM/RING FINISH:



B653W-WH BAFFLE WITH BAFFLE



BAFFLE FINISH: W, P





B651P-WH PAR20 STEPPED BAFFLE



BAFFLE FINISH: W, P, SN, CP, BZ TRIM/RING FINISH:



B611W-WH PAR30 BAFFLE WALL WASH



AVAILABLE COLOR COMBINATIONS:W-WH, P-WH, SN-SN,
CP-CP, BZ-BZ

COVER FINISH: WH. BK




B647P-WH DESIGNER BAFFLE WALL WASH PAR20



BAFFLE FINISH: W, P, SN, CP, BZ

TRIM/RING FINISH:



B644RG-WH

DESIGNER REFLECTOR WALL WASH PAR20



REFLECTOR FINISH: CL, RG, W, MB, CP, SN

TRIM/RING FINISH:




B650WH

DESIGNER WALL WASH



TRIM/RING FINISH:



B622RG-WH R/PAR30 WALL WASH REFLECTOR



REFLECTOR FINISH: CL, RG, W, MB, CP, SN, SHZ

COVER FINISH:

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ

B623MB-WH R40/PAR38 WALL WASH REFLECTOR



REFLECTOR FINISH: CL, RG, W, MB, CP, SN, SHZ

COVER FINISH:



B625CL-WH A-19 CONE REFLECTOR WALL WASH



REFLECTOR FINISH: CL, RG, W, MB, CP, SN, SHZ

COVER FINISH: WH

TRIM/RING FINISH:
WH, BK, SN, CP, CH, PB, BZ



B624W-CL

CONE REFLECTOR BAFFLE WALL WASH



BAFFLE FINISH: W, P

REFLECTOR FINISH: CL, RG

COVER FINISH: WH

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



Specifications and Dimensions subject to change without notice.

REV: MAXILUME-SPEC-05-26-2011



Catalog Number: Project Name: Type:

