

# Double Ended Linear

#### Double Ended Linear 100W 120V T3 CL 1BC

High-quality white light with superior lumen performanceHalogen Double Ended lamps provide bright, white light for work lights and security lighting. Rugged construction for busy work sites. Offered in several lengths to meet most application needs. High lumen output provides light where you need it.

#### Product data

#### • General Characteristics

Base R7s Base Information 10

Bulb T4 [Diameter: .433 inch /11mm]

Bulb Finish Clear

Operating Position Universal [Any or Universal (U)]

RatedAvgLife(See 2000 hr

Family Notes)

### • Electrical Characteristics

Energy Used 100 W Lamp Wattage Tech- 100.0 W

nical

Voltage 120 V Lamp Current 0.83 A Dimmable Yes

#### • Environmental Characteristics

Energy Efficiency Dabel (EEL)

#### • Light Technical Characteristics

Color Rendering 100 Ra8 Index
Color Temperature 2900 K
Color Temperature 2900 K

Color Temperature technical

Lumens (Brightness) 1750 Lm Luminous Efficacy 17.5 Lm/W

Lamp

#### • Product Dimensions

Insertion Length B 73.3 (min), 74.9 (nom), 76.5 (max)

mm

Overall Length C 78.3 (max) mm Diameter D 12 (max) mm

## • Luminaire Design Requirements

Pinch Temperature 350 (max) C Bulb Temperature 900 (max) C

#### • Product Data

Order code 924502234590 Full product code 924502234590

Full product name Double Ended Linear 100W 120V T3

CL 1BC

Order product name BC100T3Q/CL/1CD

Pieces per pack 1
Packing configuration 12
Packs per outerbox 12

Bar code on pack - 4

EAN1

Bar code on

outerbox - EAN3

Logistic code(s) -

12NC

ILCOS code Net weight per piece 46677116118

50046677116113

924502234590


HDG//RS-100-120-R7s-74,9

0.008 kg



# Double Ended Linear

## Dimensional drawing



Product	B (Min)	B (Norm)	B (Max)	C (Max)	D (Max)
DEComp 100W R7s 120V T11 CL	73.3	74.9	76.5	78.3	12





Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.