

Watts	Bulb	Base	Product Number	Symbols, Footnotes	Ordering Code	Volts	Pkg. Qty.‡	Description	Class Filament	LCL (In.)	MOL (In.)	Rated Avg. Life (Hrs.)(93)	Approx. MBCP*	Lumens
-------	------	------	----------------	--------------------	---------------	-------	------------	-------------	----------------	-----------	-----------	----------------------------	---------------	--------

INCANDESCENT LAMPS (BY WATTAGE) CONTINUED

75	A19	Med. ++	37472-8	▲✓	75A	120	48	Frost	C, CC-6		4%	750		1220	
		Med.	20195-4	▲✓	75A/TG	120	48	TuffGuard Coated Lamp	C, CC-6		4%	750		1220	
		Med.	15933-5	▲✓	75A/TG	130	48	TuffGuard Coated Lamp	C, CC-6		4%	750		1220	
		Med. ++	13997-1		75A 120/I PRO	130	120	Frost ProPack Lamp	C, CC-6		4%	750		1150	
		Med. ++	16801-3	▲	75A/CL/LL 12/2	120	24	Clear Long Life	C, CC-6		4%	1500		1080	
		Med. ++	13996-3		75A/CL 120/I PRO	130	120	Clear ProPack Lamp	C, CC-6		4%	750		1195	
		Med. ++	16879-9	▲	75A/WL 12/4	120	48	Soft White Long Life	C, CC-6		4%	1500		1060	
		Med. ++	16739-5	▲	75A/WL 24/4	120	96	Soft White Long Life	C, CC-6		4%	1500		1060	
		Med.	13560-8	▲	75A/NTL 12/4	120	48	Natural Light Standard	C, CC-6		4%	750		950	
		Med. ++	27083-5	▲✓	75A 12/4	120	48	Frost	C, CC-6		4%	750		1220	
		Med. ++	37473-6	▲	75A	130	48	Frost	C, CC-6		4%	750		1150	
														2120	860
		Med. ++	37406-6	▲✓	75A/99	120-130	48	Frost Extended Svc.	C, CC-6		4%	2500		1070	
														4250	930
		Med.	29360-5	▲	75A/RSVS	120-130	12	Frost Rough & Vib. Svc.	R, C-9	2½	3%	1000		712	
														1700	660
		Med.	20192-1	▲	75A/RSV/TG	120-130	12	TuffGuard Frost Rough & Vib. Svc.	R, C-9	2½	3%	1000		712	
														1700	660
		Med. ++	37525-3	▲	75A/CL	130	48	Clear	C, CC-6	3%	4%	750		1195	
														2140	885
Med. ++	37485-0	▲✓	75A/W 12/4	120	48	Soft White	C, CC-6		4%	750		1180			
Med. ++	14997-0	▲✓	75A/W 12/4	130	48	Soft White	C, CC-6		4%	1000		1100			
Med. ++	37486-8	▲	75A/W/TP 24/4	120	96	Soft White Tra-Pak	C, CC-6		4%	750		1180			
A21	Med. ++	31305-6	▲	75A21	120-130	120	Frost	C, C-9		5%	1000		1110		
												2854	858		
	Med.	20922-1	▲ (66)	75A/RH/TF 12/1	120-130	12	Frost Silicone Coated Tough Bulb	C, RC-9		5%	1000				
	Med.	20470-1	▲	75A/RH 12/1	120-130	12	Frost Rough House	C, RC-9		5%	1000		750		
												1700	730		
Med.	20018-8	▲	75A/RH/TG	120-130	12	TuffGuard Frost Rough House	C, RC-9		5%	1000		750			
												1700	730		
Med.	14345-3	▲	75A21	12	60	Frost	C, C-6		5%	1000		1100			
BR30	Med.	24903-7	▲ (66,87)	75BR30/FL/TF	120	12	Frost Silicone Coated Reflector	C, CC-6		5%	2000				
		24905-2	▲ (87)	75BR30/AGRO 6/1	120	6	Agro-Lite Plant Light	C, CC-6		5%	2000		700		
		24902-9	▲ (87)	75BR30/PK 8/1	120	8	Pink	C, CC-6		5%	2000				
ER30	Med. +++	14353-7	▲X(19,37B7)	75ER30	120	24	Elliptical Reflector	C, CC-6		6%	2000		570		
	+++	14354-5	▲X(19,37B7)	75ER30	130	24	Elliptical Reflector	C, CC-6		6%	2000		570		
BR38	Med. +++	14009-5	X(87)	75BR38/FL 6/1 PRO	130	6	Clear ProPack Lamp	C, CC-6		5%	2000		650		
	+++	15050-8	X(87)	75BR38/CLEAR 6/2	120	12	Clear	C, CC-6		5%	2000				
K19	Med.	22487-3	▲ □	75K19/DL 6/2	120	12	Director®	C, CC-6		4%	1150		1000		
R20	Med. +++	16763-5	▲ X □ (87)	75R20/LL 12/1	120	12	Frost Long Life Reflector	C, CC-6		3%	2500	800	570		