

PAR38 LED Single Optic Lamps with AirFlux Technology

19PAR38/F36 4000 DIM AF SO 6/1

Philips PAR38 LED Single Optic Lamps with AirFlux Technology improves shopping experience with superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

Product data

General Characteristics

Cap-Base	
Bulb	
Rated Avg. Life	
(Hours)	

E26 PAR38 [PAR38 mm] 50000 hr

• Light Technical Characteristics

•	
Color Code	CW
Color Designation	Cool White
Beam Angle	36 D
Beam Description	36D [Medium beam]
Correlated Color	4000 K
Temperature	
Approximate Lumens	1300 Lm
Approx. MBCP	3600 cd
CRI	81
Luminous Efficacy	68.42 Lm/W
Lamp	
Color Temp. (Kelvin)	4000 K [CCT 4000K]
Rated Luminous Flux	1300 Lm

• Electrical Characteristics

Wattage	19 W
Wattage Technical	19 W
Voltage	120 V
Line Frequency	60 Hz
Power Factor	0.9 -
Lamp Current mA	182 mA

Warnings and Safety

• Suitable for use in damp locations.





Wattage Equivalent	100 VV		
Starting Time	0.5 s		
• Environmental charac	cteristics		

Yes

Energy consumption 19 kWh kWh/1000h

- Measuring Conditions
- Switching cycle 20000X
- Product Dimensions

Overall Length C	130 mm
Diameter D	120 mm


• Product Data

Dimmable

• Not for use in totally enclosed luminaires.

PAR38 LED Single Optic Lamps with AirFlux Technology

Dimensional drawing



19PAR38/F36 4000 DIM AF SO 6/1

Product	C (Norm)	C1 (Max)	D (Norm)	D1 (Norm)
LED 19W E26 4000K PAR38 36D DIM	130	-	120	-



E26



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting