

# Candle LED

# 2.5B13/2700-E12 DIM 8/1

Philips Candle Dimmable LED Lamps offer decorative energy saving ambience with the elegant effect of incandescent candles. Available in bent, blunt and flame tip candles, their unique design provides light in all directions, giving lighting designers a long life alternative to standard incandescent sources.

# Product data

#### • General Characteristics

Cap-Base	E12
Bulb	B13
Bulb Finish	Clear
Rated Avg. Life	25000 hr
(Hours)	
Nominal Lifetime	25000 hr
hours	

## • Light Technical Characteristics

Color Code Color Designation	WW Warm White
Correlated Color	2700 K
Temperature Approximate Lumens	180 Lm
CRI	80
Luminous Efficacy	72 Lm/W
Lamp	
Color Temp. (Kelvin)	2700 K [CCT 2700K]
Rated Luminous Flux	180 Lm
LLMF - end nominal	70 %
lifetime	
Colour consistency	6 steps

## • Electrical Characteristics

Wattage	2.5 W
Voltage	120 V
Line Frequency	60 Hz
Power Factor	0.5 -
Lamp Current mA	39 mA
Dimmable	Yes
Wattage Equivalent	25 W
Rated Wattage	2.5 W



Starting Time	
Warm-up Time to	
60% Light Outp	
Suitable for accent	
lighting	

0.5 (max) s instant full light No

#### • Environmental characteristics

Energy Efficiency A+ Label (EEL) 3 kWh Energy consumption kWh/1000h

Measuring Conditions

Switching cycle 50000X

• Product Dimensions

Overall Length C Diameter D

# • Product Data

Product number Full product name Short product name Pieces per Sku eop\_pck\_cfg Skus/Case Bar code on pack Bar code on case Logistics code(s) eop\_net\_weight\_pp

435149 2.5B13/2700-E12 DIM 8/1 2.5B13/2700-E12 DIM 8/1

8 46677435141 50046677435146 929000279904 0.062 kg

111 mm

39 mm


1

8



# Candle LED

# Dimensional drawing



# 2.5B13/2700-E12 DIM 8/1

Product	C (Norm)	D (Norm)
LED 2.5W E12 2700K 120V B13 Clear	111	39



E12



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting