

RhinoBox temporary power centers with GFCI protection E-series

Product description

50A input
20A, 30A, 50A output
120/240 V/AC (max.)



RB300ME

Features

- Safely centralize and distribute temporary power on the job site
- Unique patented “stackable” design allows multiple RhinoBox units to lock together for safe transport and storage
- NEMA 3R enclosures designed with two devices per circuit
- Available with manual or automatic GFCI reset configurations
- Weatherproof receptacle covers protect from damage and weather
- Flip-up circuit breaker cover prevent accidental tripping


RhinoBox E-series

Rating A	V/AC	Distribution devices	Receptacle ratings	Protection		Catalog no.*	
				Overload	GFCI		
50	120/240 Max.	(6) WR duplex receptacles	20A, 125V	✓	✓	□ RB300ME	•
		(1) Locking receptacle	30A, 250V	✓	—		
		(1) Locking inlet	50A, 125/250V	—	—		
		(1) Locking outlet	50A, 125/250V	—	—		
50	120/240 Max.	(6) WR duplex receptacles	20A, 125V	✓	✓	□ RB300ME-L5	•
		(1) Locking receptacle	30A, 125V	✓	—		
		(1) Locking inlet	50A, 125/250V	—	—		
		(1) Locking outlet	50A, 125/250V	—	—		
50	120/240 Max.	(6) Single receptacles	20A, 125V	✓	✓	□ RB301ME	•
		(1) Locking receptacle	30A, 250V	✓	—		
		(1) Locking inlet	50A, 125/250V	—	—		
		(1) Locking outlet	50A, 125/250V	—	—		
50	120/240 Max.	(6) Locking receptacles	20A, 125V	✓	✓	□ RB302ME	•
		(1) Locking receptacle	30A, 250V	✓	—		
		(1) Locking inlet	50A, 125/250V	—	—		
		(1) Locking outlet	50A, 125/250V	—	—		

*Automatic GFCI reset configurations are available. When ordering automatic RhinoBox replace “M” in Catalog no. with “A”.
Example: RB300AE = Automatic; RB300ME = Manual.



5-20R L5-20R L6-30R



Plug Non-NEMA 50A 125/250V CA Standard
Receptacle Non-NEMA 50A 125/250V CA Standard

Testing & code compliance: cETLus listed for outdoor use - NEMA 3R products. Complies with NEC® Articles 525 & 590 & OSHA Reg. 29CFR, Part 1926, Subpart K, 1926.404, GFCI requirements. Conforms to UL1640 and CSA C22.2, no. 14. **Material characteristics:** Enclosure: Cold-rolled 18 gauge steel. Legs: Cold-rolled 10 gauge steel.

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-30