

Cable-Cream® Cable Pulling Lubricant



- Advanced formula, light yellow cream makes pulling faster and easier.
- Compatible with all cable insulation types.
- Dries slowly to a thin, non-conductive, non-hardening residue.
- Adheres well to the cable without messy dripping. Reduces waste.
- Cleans up easily. Non-staining.
- Won't break down or separate after exposure to freezing cold or blistering heat.
- Environmentally safe/non-hazardous.

SPECIFICATIONS

| | |
|--------------------|---|
| Weight | CRM-Q - 2.3 lbs. (1 kg) CRM-5 - 42 lbs. (19.1 kg) CRM-1 - 9.5 lbs. (4.3 kg) |
| Viscosity | 30,000 - 45,000 CPS |
| PH Range | 7.0 - 8.0 |
| Average COF | 0.11 |

| CAT. NO. | UPC NO. | DESCRIPTION |
|----------|---------|--|
| CRM-Q | 35207 | Cable-Cream One Quart Squeeze Bottle (.95 l) |
| CRM-1 | 35208 | Cable-Cream One Gallon (3.79 l) |
| CRM-5 | 35209 | Cable-Cream 5 Gallons (18.93 l) |

Cable-Gel® Cable Pulling Lubricant



- Polymer-based, no silicon lubricant offers lower friction and easier pulling.
- Compatible with all cable insulation types.
- Cleans up quickly. Non-staining.
- Higher lubricity than competitive products.
- Will not cement itself to the pipe.
- Dries slowly.
- Can be applied by hand or pump.
- Will not break down or separate after exposure to heat or cold.
- Environmentally safe/non-hazardous.

SPECIFICATIONS

| | |
|--------------------|---|
| Weight | GEL-Q - 2.3 lbs. (1 kg) GEL-1 - 8.5 lbs. (3.9 kg) GEL-5 - 45 lbs. (20.4 kg) GEL-55 - 498 lbs. (225.9 kg) |
| Viscosity | 8,000 - 12,000 CPS |
| PH Range | 7.0 - 8.0 |
| Average COF | 0.18 |

| CAT. NO. | UPC NO. | DESCRIPTION |
|----------|---------|--|
| GEL-Q | 35211 | Cable-Gel One Quart Squeeze Bottle (.95 l) |
| GEL-1 | 35212 | Cable-Gel One Gallon (3.79 l) |
| GEL-5 | 35213 | Cable-Gel 5 Gallons (18.93 l) |

Winter-Gel™ Cable Pulling Lubricant



- Winter-Gel will not freeze until -25° F (-31° C).
- Reduces friction for easy pulling.
- Compatible with all cable insulation types.
- Cleans up quickly and easily.
- High lubricity.
- Can be used all year long.
- Environmentally safe.

SPECIFICATIONS

| | |
|--------------------|--|
| Weight | WGEL-Q - 2.3 lbs. (1 kg) WGEL-1 - 9 lbs. (4.1 kg) WGEL-5 - 44 lbs. (20 kg) |
| Viscosity | 10,000 - 14,000 CPS |
| PH Range | 7.0 - 8.0 |
| Average COF | 0.21 |

| CAT. NO. | UPC NO. | DESCRIPTION |
|----------|---------|--|
| WGEL-Q | 35215 | Winter-Gel Pulling Lube One Quart Squeeze Bottle (.95 l) |
| WGEL-1 | 35216 | Winter-Gel Pulling Lube One Gallon (3.79 l) |
| WGEL-5 | 35217 | Winter-Gel Pulling Lube 5 Gallons (18.93 l) |