BURNDY® Products FST

TYPES Y750HS AND Y750-2HS RUBBER COVERED HEAD

750 REVOLVER HYPRESS™

HYDRAULIC HAND OPERATED TOOL — 12 TON CRIMP FORCE

CONDUCTOR RANGE: #12-750 KCMIL CU/AL AND #4-556.5 KCMIL ACSR

The BURNDY® Y750HS Series HYPRESS™ is a wide mouth (1.65″) hand operated hydraulic 12 ton crimping tool for use on virtually all compression applications. The C-shaped head rotates 355° relative to the handle and is mated to a patented rapid advance pump. The Y750HS provides easy tapping, splicing, and terminating of overhead lines, the full line of HYGROUND™ compression grounding connectors, NEC cable connections, and N30-N650 Navy cable connections.

The Y750HS accepts all BURNDY® "U" dies for use on conductor ranges of #12-750 kcmil AL/CU and #4-556.5 kcmil ACSR conductors.

The Y750-2HS HYPRESS™ has a rubber-covered head and handles for tool impact protection.



BENEFITS

- Covers a wide range of applications with a lightweight, self-contained system and provides easy tool removal from continuous conductors with its C-shaped head.
- Easy tool positioning with its 355° head rotation.
- Patented rapid advance pump for faster crimps.
- Exposed positive die lock buttons for easy die change out and die retention.
- Handle trigger drain for convenient ram retraction.
- Quality assurance is provided with an audible "Pop-Off" pressure relief valve.
- Comfort grip handles help ease operator fatigue with continuous use.

SPECIFICATIONS

Force developed: 12 tons

Weight: 14.5 lbs. (5.4 kg) Length: 23.5" (7162 mm) Height: 2.75" (838 mm) Width: 8.0" (2438 mm) Jaw opening: 1.65" (42 mm)

FOR USE ON

Tension Sleeves

Copper #8 sol.-500 kcmil Aluminum #8 sol.-587-2 kcmil ACSR #4-556.5 kcmil

Taps

Copper #14 sol.-500 kcmil Aluminum #8-500 kcmil

Aerial Cable

Copper #6-500 kcmil

· Terminals & Splices

Aluminum #8-750 kcmil Copper #8-750 kcmil ACSR #4-556 kcmil


ACCESSORIES:

Cat. No. Description

Y750HSCASE Plastic Carrying Case for

Y750HS and Y750-2HS

Features



BENEFITS (Continued)

- Long life expectancy from the company that provided the industry with the first selfcontained hydraulic tool in 1934.
- Rubber covered head and handles on Y750-2HS for tool impact protection.
- Supplied with high impact plastic carrying case.
- 5-year limited warranty.

N-25