

**Contact**

Copper LAN Product Inquiry  
Phone: 717-354-6200  
berktek.support@nexans.com

## LANmark-350 Riser Rated Premium Category 5e UTP

LANmark-350 Riser

Part Number: 10032426

Berk-Tek's LANmark-350 Premium Category 5e UTP cables are designed to meet the most advanced UTP horizontal cable applications. Tested up to 350 MHz, the guaranteed performance of this cable far exceeds the ANSI/TIA/EIA-568-C.2 and ISO/IEC 11801 horizontal cable requirements for PS-NEXT, attenuation, structural return loss, attenuation-to-crosstalk ratio (ACR) and impedance, making it ideal for high-end transmission links supporting today's networking protocols.

### Description

#### Berk-Tek LANmark-350, Performance Guaranteed

Before any cable can display the **Berk-Tek LANmark-350** legend, it must pass factory tests with a **minimum of margin of 3dB for ACRF & PSACRF, 5 dB for NEXT & ACR and 6dB of margin for PSNEXT & PSACR beyond the CAT 5e standard**. If the margin is missing, so is the legend. That is our guarantee to you.

Your business demands continuous performance from your IT network, so our specifications aren't simply numbers on the page. They define the way that we do business. This means that you are **guaranteed** industry-leading performance and quality for all Berk-Tek products.

Some other manufacturers talk about "typical" values, at Berk-Tek, we hold ourselves to a higher standard. We won't talk about typicals, we talk about what is true, guaranteed, and independently verified.

Keep your business running by relying on Berk-Tek.

**Perform Beyond Expectations... Choose Berk-Tek.**

#### Construction

Bare copper wire insulated with polyethylene. Two insulated conductors twisted together to form a pair and four such pairs cabled to form the basic unit jacketed with flame-retardant PVC.

#### Flame Rating

- Riser - UL 1666, CMR
- ETL Listed

#### Features

- Small, round design
- ETL verified to TIA/EIA-568-C.2 and ISO/IEC 11801
- RoHS Compliant

#### Benefits

- Reliably supports 100BASE-TX Ethernet
- Reduced installation costs and maintenance
- Characterized to 450 MHz, 350 MHz greater than standard
- Lower bit error rates, increases network efficiency and uptime



#### Standards

International ISO/IEC 11801

National ANSI/TIA-568-C.2; UL 444

**Contact**

Copper LAN Product Inquiry  
Phone: 717-354-6200  
berktek.support@nexans.com

## LANmark-350 Riser Rated Premium Category 5e UTP

LANmark-350 Riser

Part Number: 10032426

### Characteristics

Construction characteristics	
Type of cable	UTP
Colour	Blue
Dimensional characteristics	
Length per reel	1000.0 ft
Number of pairs	4
Usage characteristics	
Packaging	Box
Field of application	Indoor
Category	Cat. 5e
Fire safety	CMR - Riser Rated

## LANmark-350 Riser Rated Premium Category 5e UTP

LANmark-350 Riser  
 Part Number: 10032426

### LANmark-350 Parametric Data: Electrical

FQ = Frequency (MHz) / TIA = TIA Spec / PG = Product Guarantee

FQ	RL (dB)		NEXT (dB)		PSNEXT (dB)		ACRF (dB)		LCL/TCL
	TIA / PG	TIA / PG	TIA / PG	TIA / PG	TIA / PG	TIA / PG	TIA / PG	PG	
1	20.00 / 20.00	65.30 / 70.30	62.30 / 68.30	63.80 / 66.80	40.00				
4	23.00 / 23.30	56.30 / 61.30	53.30 / 59.30	51.80 / 54.70	40.00				
10	25.00 / 25.50	50.30 / 55.30	47.30 / 53.30	43.80 / 46.80	40.00				
16	25.00 / 25.50	47.20 / 52.30	44.20 / 50.30	39.70 / 42.70	38.00				
20	25.00 / 25.50	45.80 / 50.80	42.80 / 48.80	37.80 / 40.70	37.00				
31.25	23.60 / 24.40	42.90 / 47.90	39.90 / 45.90	33.90 / 36.90	35.10				
62.5	21.50 / 22.70	38.40 / 43.40	35.40 / 41.40	27.90 / 30.80	32.00				
100	20.10 / 21.40	35.30 / 40.30	32.30 / 38.30	23.80 / 26.80	30.00				
150	— / 20.50	— / 37.70	— / 35.70	— / 23.30	28.20				
200	— / 19.80	— / 35.80	— / 33.80	— / 20.70	27.00				
250	— / 19.20	— / 34.30	— / 32.30	— / 18.80	26.00				
300	— / 18.80	— / 33.20	— / 31.20	— / 17.30	25.20				
350	— / 18.40	— / 32.20	— / 30.20	— / 15.90	24.60				
400	— / 18.10*	— / 31.30*	— / 29.30	— / 14.70	24.00*				

  

FQ	IL (dB/100 m)		ACR (dB/100 m)		PSACR (dB/100 m)		PSACRF (dB/100 m)		EL TCTL
	TIA / PG	TIA / PG	TIA / PG	TIA / PG	TIA / PG	TIA / PG	TIA / PG	PG	
1	2.00 / 2.00	63.30 / 68.30	60.30 / 66.30	60.80 / 63.80	35.00				
4	4.10 / 4.00	52.20 / 57.30	49.20 / 55.30	48.80 / 51.70	23.00				
10	6.50 / 6.40	43.80 / 48.90	40.80 / 46.90	40.80 / 43.80	15.00				
16	8.20 / 8.10	39.00 / 44.10	36.00 / 42.10	36.70 / 39.70	10.90				
20	9.30 / 9.20	36.50 / 41.60	33.50 / 39.60	34.80 / 37.70	9.00				
31.25	11.70 / 11.60	31.20 / 36.30	28.20 / 34.30	30.90 / 33.90	5.10				
62.50	17.00 / 16.80	21.40 / 26.60	18.40 / 24.60	24.90 / 27.80	—				
100	22.00 / 21.70	13.30 / 18.60	10.30 / 16.60	20.80 / 23.80	—				
150	— / 27.20	— / 10.40	— / 8.40	— / 20.30	—				
200	— / 32.10	— / 3.70	— / 1.70	— / 17.70	—				
250	— / 36.50	— / -2.10	— / -4.10	— / 15.80	—				
300	— / 40.50	— / -7.40	— / -9.40	— / 14.30	—				
350	— / 44.40	— / -12.20	— / -14.20	— / 12.90	—				
400	— / 48.00*	— / -16.80*	— / -18.80*	— / 11.70*	—				

\*Values provided for reference only

### LANmark-350 Riser UTP Physical Data

Technical Data - Physical			Color Code		
Conductor	24 AWG Bare Copper		Pair-1	White/Blue	Blue
Conductor diameter - in. (mm)	0.020	(0.51)	Pair-2	White/Orange	Orange
Insulated conductor dia.-in.(mm)	0.036	(0.91)	Pair-3	White/Green	Green
Cable diameter - in. (mm)	0.19	(4.83)	Pair-4	White/Brown	Brown
Nom. cable wt.-lb./kft. (kg/kft)	20	(9.07)	Temperature Rating (degrees C)		
Max. installation tension - lb. (N)	25	(110)	Installation	0 to +50	
Min. bend radius - in. (mm)	1.00	(25.40)	Operation	-20 to +75	

### LANmark-350 Riser Technical Data - Parametric Measurements

Mutual Capacitance	4.9 nF/100 m max.	Pair to Ground Unbalance	330 pF/100 m max.
--------------------	-------------------	--------------------------	-------------------

## LANmark-350 Riser Rated Premium Category 5e UTP

**LANmark-350 Riser**

<b>DC Resistance</b>	9.38 Ohms/100 m max.	<b>Velocity of Propagation</b>	70% nom.
<b>Skew</b>	45 ns/100 m max.	<b>DC Resistance unbalance</b>	5% max.

### Supported Category 5e Applications

STANDARD	APPLICATION	SPEED
IEEE 802.3	1000BASE-T	1 Gb/s
ATM	155Mb/s	155 Mb/s
IEEE 802.3	100BASE-TX	100 Mb/s
CDDI		100 Mb/s
IEEE 802.3	10BASE-T	10 Mb/s

### LANmark-350 UTP Riser Jacket Legend

BERK-TEK LANMARK-350 24 AWG CMR 75C C(ETL)US MEETS UL 444 ETL VERIFIED TIA-568-C.2 CAT 5E & ISO/IEC 11801 CAT 5 [ANY APPLICABLE PATENTS] [DATECODE] [SEQ#] FT

### Selling information

PLEASE NOTE: In the interest of product improvement, Berk-Tek, a Nexans company may make improvements or changes in the products, the programs or services described at any time without notice. Additionally, the information contained herein may include typographical errors or technical inaccuracies. Changes will be periodically made to address any such issues.