



OVERLOAD RELAY 10...40 A FOR MOTOR PROTECTION SIZE S0, CLASS 10 CONTACTOR ASS. MAIN CIRCUIT: SPR.-LOAD.TERM. AUX.CIRCUIT: SPR.-LOAD.TERM. MANUAL-AUTOM.-RESET

product brand name	SIRIUS
Product designation	solid-state overload relay

General technical data:

Size of contactor can be combined company-specific	S0
Active power loss total typical	4.5 W
Insulation voltage	690 V
<ul style="list-style-type: none"> with degree of pollution 3 Rated value 	690 V
Surge voltage resistance Rated value	6 kV
Protection class IP	IP20
<ul style="list-style-type: none"> on the front of the terminal 	IP20
Vibration resistance	1-6 Hz, 15 mm; 6-500 Hz, 20 m/s ² ; 10 cycles
Type of assignment	2
Type of protection	II (2) G [Ex e] [Ex d] [Ex px] II (2) D [Ex t] [Ex p]
Equipment marking	F
<ul style="list-style-type: none"> acc. to DIN EN 61346-2 acc. to DIN EN 81346-2 	F

Ambient conditions:

Installation altitude at height above sea level maximum	2 000 m
Ambient temperature	-25 ... +60 °C
<ul style="list-style-type: none"> during operation during storage during transport 	-40 ... +80 °C
Relative humidity during operation	95 %

Main circuit:	
Number of poles for main current circuit	3
Adjustable response value current of the current-dependent overload release	10 ... 40 A
Operating voltage <ul style="list-style-type: none"> • at AC-3 Rated value maximum 	690 V
Operating frequency Rated value	50 ... 60 Hz
Operating current <ul style="list-style-type: none"> • at AC-3 — at 400 V Rated value 	40 A

Auxiliary circuit:	
Number of NC contacts <ul style="list-style-type: none"> • for auxiliary contacts — Note 	1 for contactor disconnection
Number of NO contacts <ul style="list-style-type: none"> • for auxiliary contacts — Note 	1 for message "tripped"
Number of CO contacts <ul style="list-style-type: none"> • for auxiliary contacts 	0
Design of the auxiliary switch	integrated
Operating current of the auxiliary contacts at AC-15 <ul style="list-style-type: none"> • at 24 V • at 110 V • at 120 V • at 125 V • at 230 V 	4 A 4 A 4 A 4 A 3 A
Operating current of the auxiliary contacts at DC-13 <ul style="list-style-type: none"> • at 24 V • at 60 V • at 110 V • at 125 V • at 220 V 	2 A 0.55 A 0.3 A 0.3 A 0.11 A

Protective and monitoring functions:	
Trip class	CLASS 10
Design of the overload circuit breaker	electronic

UL/CSA ratings:	
Contact rating of the auxiliary contacts acc. to UL	B600 / R300

Short-circuit:	
Design of the fuse link <ul style="list-style-type: none"> • for short-circuit protection of the main circuit 	

- required
- for short-circuit protection of the auxiliary switch required

Fuse gG: 80 A
fuse gG: 6 A

Installation/ mounting/ dimensions:

mounting position	any
Mounting type	direct mounting
Height	109 mm
Width	45 mm
Depth	85 mm
Required spacing	
<ul style="list-style-type: none"> • with side-by-side mounting <ul style="list-style-type: none"> — forwards — Backwards — upwards — downwards — at the side • for grounded parts <ul style="list-style-type: none"> — forwards — Backwards — upwards — at the side — downwards • for live parts <ul style="list-style-type: none"> — forwards — Backwards — upwards — downwards — at the side 	<ul style="list-style-type: none"> 0 mm 0 mm 0 mm 0 mm 0 mm 6 mm 0 mm 6 mm 6 mm 6 mm 6 mm 6 mm 6 mm 6 mm

Connections/ Terminals:

Product function	
<ul style="list-style-type: none"> • removable terminal for auxiliary and control circuit 	Yes
Type of electrical connection	
<ul style="list-style-type: none"> • for main current circuit • for auxiliary and control current circuit 	<ul style="list-style-type: none"> spring-loaded terminals spring-loaded terminals
Arrangement of electrical connectors for main current circuit	Top and bottom
Type of connectable conductor cross-section	
<ul style="list-style-type: none"> • for main contacts <ul style="list-style-type: none"> — single or multi-stranded — finely stranded with core end processing 	<ul style="list-style-type: none"> 1x (1 ... 10 mm²) 1x (1 ... 6 mm²)

— finely stranded without core end processing	1x (1 ... 6 mm ²)
• for AWG conductors for main contacts	1x (18 ... 8)
Type of connectable conductor cross-section	
• for auxiliary contacts	
— single or multi-stranded	1x (0,5 ... 1,5 mm ²), 2x (0,5 ... 1,5 mm ²)
— finely stranded with core end processing	1x (0.25 ... 1.5 mm ²), 2x (0.25 ... 1.5 mm ²)
— finely stranded without core end processing	1x (0.25 ... 1.5 mm ²), 2x (0.25 ... 1.5 mm ²)
• for AWG conductors for auxiliary contacts	1x (24 ... 16), 2x (24 ... 16)

Mechanical data:

Size of overload relay	S0
-------------------------------	----

Communication/ Protocol:

Protocol is supported	
• IO-Link protocol	No
Type of voltage supply via input/output link master	No

Electromagnetic compatibility:

EMC emitted interference	
• acc. to IEC 60947-1	CISPR 11, environment B (residential area)
EMI immunity acc. to IEC 60947-1	corresponds to degree of severity 3
Conducted interference due to burst acc. to IEC 61000-4-4	2 kV (power ports), 1 kV (signal ports) corresponds to degree of severity 3
Conducted interference due to conductor-earth surge acc. to IEC 61000-4-5	2 kV (line to earth) corresponds to degree of severity 3
Conducted interference due to conductor-conductor surge acc. to IEC 61000-4-5	1 kV (line to line) corresponds to degree of severity 3
Field-bound parasitic coupling acc. to IEC 61000-4-3	10 V/m
Electrostatic discharge acc. to IEC 61000-4-2	6 kV contact discharge / 8 kV air discharge

Display:

Display version	
• for switching status	Slide switch

Certificates/ approvals:

General Product Approval	EMC	For use in hazardous locations
--------------------------	-----	--------------------------------



Declaration of Conformity	Test Certificates	Shipping Approval
---------------------------	-------------------	-------------------



[spezielle Prüfbescheinigungen](#)

[Typprüfbescheinigung/Werkszeugnis](#)



Shipping Approval	other
-------------------	-------



[Umweltbestätigung](#)

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RB30261VE0>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RB30261VE0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RB30261VE0&lang=en





last modified:

29.06.2015