

Eaton XT IEC control relay

XTOM2P4AC1

Dimensions:

- Height: X
- Length: X
- Width: X

Notes: Observe the maximum permissible fuse of the contactor with direct device mounting. Clearance of at least 5 mm is required between the overload relays when fitted directly to contactor.

Warranties: No Data

Specifications:

- **Contact Configuration:** 1NO-1NC
- **Frame Size:** 45 mm - mini
- **Mounting:** Direct
- **Overload Range:** 1.6-2.4A
- **Trip Type:** 10A
- **Type:** XT IEC Miniature Overload Relay

Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [XTOM AutoCAD 2D Footprint \(mm\)](#)
- [XTOM 3D Inventor](#)
- [XTOM 2D Drawing Xchange](#)
- [XTOM AutoCAD 2D Footprint](#)
- [XTOM 2D PDF](#)
- [XTOM 3D Model Xchange](#)
- [Eaton Specification Sheet - XTOM2P4AC1](#)
- [Global Data Sheet - XTOM2P4AC1](#)

Certifications:

- UL Listed
- CSA Certified
- IEC 60947
- EN 60947

Product compliance:

- CE Marked



- ATEX Compliant
- RoHS Compliant

© 2016 Eaton. All rights reserved.