U-Line™ Interchanger Sealed 15 and 20 Amp Plugs

For U-Line™ 20 Amp Receptacles. Explosionproof, Dust-Ignitionproof

These raintight ① plugs also fit NEMA 5-20R or 6-20R receptacles in nonclassified areas. Choice of Aluminum or Thermoplastic Polyester Plug.

NEC/CEC: Class I, Division 1 and 2 Groups B, C, D Class II, Division 1 and 2 Groups F, G Class III NEMA 3, 3R, 7BCD, 9FG

Applications

- U-Line[™] Interchanger ECP plug: suitable for use in such areas as refineries, petrochemical plants, and other areas subject to where ignitable gases are present.
- NCP Plug: ideal where moisture or corrosion is a constant problem, such as production facilities on marine platforms, and pipeline transportation facilities.

Features

- Unique blade-type, brass contacts exert constant pressure along entire contact surface and provide superior electrical contact.
- Insulators provide superior dielectric and mechanical strength and lowest arc tracking.
- Longer plug housing for better gripping and easier plug insertion and withdrawal.


- Plugs fits any standard non-explosionproof receptacle (NEMA 5-15R, 5-20R, or 6-20R) as well as U-Line™ explosionproof receptacles.
- ECP plug: a twist of the plug produces audible "click" to indicate fast make and break of built-in switch contacts.
 Twisting plug locks it in place and cannot be accidentally pulled out.
- NCP plug: special neoprene watertight plug bushing accommodates flexible cord ranging from .538" to .639" diameter.

Standard Materials

- ECP plug: copperfree (less than 4/10ths of 1%) aluminum
- NCP plug: 30% glass-reinforced thermoplastic polyester

		Diagram	Wire/ Pole	Cable Dia., (Inches)	Catalog Number	
	Amp				125 Vac	250 Vac
J-Line™ Interchanger ECP	Standard Plug					
	15		2W, 3P	0.538 to 0.639	ECP-1523	
	20	•	2W, 3P	0.538 to 0.639	ECP-2023	
	20	•	2W, 3P	0.538 to 0.639		ECP-20232
ICP Plug						
	15	\bigcirc	2W, 3P	0.538 to 0.639	NCP-1523	
	20	<u>•</u>	2W, 3P	0.538 to 0.639	NCP-2023	
	20		2W, 3P	0.538 to 0.639		NCP-20232

Dimensions in Millimeters (Inches)



① Raintight when mated with receptacle.

