E-Z-Ground® Grounding Systems

Ground Rods

Sectional type Ground Rods

 Sectional type ground rods have the same high-quality as regular copper bonded steel ground rods, and are threaded top and bottom





Cat. No.	Trade Size		Rod Size (nominal diameter x length)		Plating	Thread	Standard	Weight per 100	
	in.	ft.	mm	m	Thickness	Size	Packaging	lb.	kg
5006LS	1/2	6	12.7	1.8	10 mils	9/16–12	5	410	189
5008LS		6						546	248
5010LS		8		2.4				682	309
6256S	5/8	6	15.8	3.0	5 mils	5/8–11		481	230
6258S		8			10 mils			670	308
6260S		10						837	384
7506S		6		1.8	5 mils	3/4–10		774	160
7508S	3/4	8	19.0	2.4	10 mils			992	450
7510S		10		3.0				1040	562
1010S	1	10				8–1	1	2248	1020

CSA lists rods 1/2 in. and larger, 10 ft. and longer.

Couplings

• Threaded couplings are made of high-strength, corrosion resistant alloy. Streamlined design reduces driving friction. Couplings are tapped for use on all standard threaded sectional rods







Cat. No.	Rod Diameter (in.)	Thread Size	Standard Packaging	Weight per 100 (lb.)
50LC	1/2	9/16 in. – 12 UNS		17
60C	5/8	5/8 in. – 11 UNS	25	25
70C	3/4	3/4 in 10 UNS		38
80C	1	1 in. – 8 UNS	10	75