

Air Conditioner Accessories

Neoprene Gasket Kit

- Replacement for standard supplied gasket.
- Self-adhesive cellular neoprene gasket.
- Supplied in 10 foot rolls, 0.19"x0.75".
- For side mount units greater than 3500 BTU/H, two gasket kits are required.

Part No. **1481DJ10**

Replacement Grill

- Replacement grill for air conditioners.
- Packaged individually.

| Black Part No. | RAL 7032 Beige Part No. | Use with Air Conditioner |
|----------------|-------------------------|--------------------------|
| PG3BK | PG3RAL | DTS1200 - DTS3500 |
| PG5BK | PG5RAL | DTS8000 - DTS12000 |
| n/a | AFF1 | DTT4500 |

Climate Control

Replacement Filters

- Packaged in quantities of 5.
- Made of synthetic fibers.
- Re-usable up to 20 times.
- 100% resistant to humidity.
- Filters have a mass filtering level of 67%.

| Part No. | Dimensions | | Use With Air Conditioner | Filter Density (g/m ²) |
|-----------------|------------|--------------|--------------------------|------------------------------------|
| | A | B | | |
| DTSF3150 | inch mm | 8.30 210 | 8.30 210 | DTS1200 - DTS6000 150 |
| DTSF5150 | inch mm | 11.00 280 | 11.00 280 | DTS8000 - DTS12000 150 |
| DTTF5150 | inch mm | 11.81 300 | 11.81 300 | DTT4500 150 |

Remote Door Switch

- Permits convenient door activated on-off function of air conditioners. Mounts to flange of any Hammond enclosure.
- Can be wired normally open or normally closed.
- 115/230 V AC

Part No. **FLKDS**



Lifting Lugs

- Packaged in quantities of 2.
- Used for lifting, transporting and installation of air conditioners.
- 8 mm diameter.
- For use with DTS3500 - DTS12000 and DTT4500.

Part No. **LL8**

Water Condensate Evaporator



- High performance evaporation kit
- Easy to retrofit on any cooling unit

Part No. **KVDTX**

| Technical Data | |
|------------------------|---|
| Max. Water Volume | 13.5 oz (400 ml) |
| Evaporation Rate | 3.4 oz/hr (100 ml/hr) |
| Electrical Data | |
| Voltage(s) | 230v / 115v |
| Frequency | 50/60 Hz |
| Voltage Range | 100-240v |
| Max. Power | 125 W |
| Power Range | 20-110 W |
| Nominal Current | 0.5 A (230v) / 0.8 A (115v) |
| Starting Current | 1.3 A |
| Zero Water Current | 0.09 A (230v) / 0.18 A (115v) |
| Mechanical Data | |
| Height x Width x Depth | 3.35" x 10.35" x 4.00" (85 x 263 x 102 mm) |
| Finish | Stainless Steel |
| Weight | 2.6 lbs (1.175 Kg) |

Technical references and DXF downloads available at www.hammsg.com

All dimensions in inches unless specified otherwise