

# A. System Overviev

#### B1. Cable Ties

# B2. Cable

#### B3. Stainless Steel Cable Ties & Accessories

#### C1. Wiring Duct

#### C2. Abrasion Protection

# C3. Cable Management

# D1. Terminals

#### D2. Power Connectors

## D3. Grounding Connectors

# E1. Labeling Systems

# E2.

#### E3. Pre-Printed & Write-On Markers

#### E4. Permanent Identification

### E5. Industrial Safety Solutions


## F. Keystone Cabling Systems

### G. Part Number Index

# CALUS ABMQ Multiple Bridge Adhesive Backed Cable Tie Mounts

- Multiple cable tie bridges on one mount speeds installation of cable bundles by reducing the number of mounts applied
- Dovetail connection system provides alignment and a joining method to expand routing capabilities
- V-groove allows for easy separation into two mounts with two bridges each for separate applications
- 4-way cable tie bridges allow cable bundles to be secured perpendicular to the mount for even spacing or inline to secure a bundle in multiple places
- Large adhesive surface area provides long-term reliability and keeps product in place despite heavy load or high stress





Part Number	Used with Cable Ties	Material	Color	Environment	Mounting Method	Std. Pkg. Qty.	Std. Ctn. Qty.
ABMQS-A-C	M,I,S	ABS	White	Indoors	Rubber	100	1000
ABMQS-A-Q		ABS	White	Indoors	Rubber	25	250
ABMQS-A-Q20		ABS	Black	Indoors	Rubber	25	250

# ABMQ Mounts for Installation with Screws or User-Supplied Adhesive


LIGILD							
ABMQS-S6-C	M, I, S	ABS	White	Indoors/High Temp	Two #6 M3 Screws	100	1000

‡Cable tie cross section sizes: M = Miniature, I = Intermediate, and S = Standard.

# Tak-Ty® Hook & Loop Cable Tie Mounts

- For use with hook and loop cable ties, see page B1.83, B1.84
- Unique cradle design provides maximum stability for cable bundle
- For indoor use only
- Dimensions: 1.10"L x 1.12"W x 0.34"H (27.9mm x 28.4mm x 8.6mm)





	Used with			Max. Static Load		Mounting Method	Std. Pkg.	Std. Ctn.
Part Number Cable Ties‡	Material	Color	Lbs.	g	Qty.		Qty.	
ABMT-A-C	HLT, HLS, TTS, UCT	Nylon 6.6	Natural	0.38	174	Pre-Installed Rubber Adhesive	100	1000
ABMT-A-C20			Black				100	1000
ABMT-S6-C			Natural	_	_	#6 (M3) Screw	100	1000
ABMT-S6-C20			Black				100	1000
ABMT-S6-C60		Flame Retardant Nylon 6.6	Black				100	1000
ABMT-S6-C69			Natural				100	1000

‡Cable tie cross section sizes: HLT = Tak-Ty™ Hook & Loop Ties, HLS = Tak-Ty™ Hook & Loop Strip Tie, TTS = Tak-Tape™ Roll, UCT = Ultra-Cinch™ Tie.

<sup>\*</sup>For proper selection of adhesives see page B2.53.