Structural Attachments - Beam



Structural Attachments - Beam

305 Stainless Steel Beam Clamp, **Top Mount**

- Pressed steel beam clamp
- Structural attachment to top flange of metal
- Structural attachment to top hange of me beams, purlins, channel, or angle iron
 Conforms with Federal Specification
 WW-H-171 (Type 23), Manufacturers
 Standardization Society ANSI*/MSS-SP-58 (Type 19)



Material: Stainless Steel 304

Part Number	Description	F ↓
3050037S4	3/8" Rod, 5/8" Max Flange	500 lb
3050050S4	1/2" Rod, 5/8" Max Flange	1,130 lb

Set screw must be tightened and torqued onto the sloped side of the I-beam, channel, or angle iron flange. Recognizing that torque wrenches are generally not used or available on many job sites, the setscrew should be tightened so it contacts the I-beam and then an additional 1/4 to 1/2 turn added.

BC Beam Clamp

• Easy installation to beam flanges



Material: Spring Steel Finish: CADDY ARMOUR



Part Number	Description	F	
BC	1/4" Rod, 7/16" Hole, 1/2" Max Flange	100 lb	100 pc

Setscrew must be tightened and torqued onto the sloped side of the I-beam.



Ph: 1-800-25-CADDY www.erico.pentair.com