

Cable Ties

Catalogue Number Construction

L **4** **18** **HS** - **9** **M**

Product Prefix
P - Plain Bagged Cable Ties
L - Cable Ties

Length
18 lb.
30 lb.
40 lb.
50 lb.
120 lb.
175 lb.
250 lb.

Tensile Strength

Type of Product
Nylon 66 - Leave Blank
Heat Stabilized - HS
(Black and Natural Colour Only)
Fluorescent - FL
Mounting Head - MH
Pushmount - PM
Pushmount Releasable - PMR
Releasable - R
Restricted Bundle - TB
Identification - ID

Colour
See Colour Table

Quantity
Q - 25 pack
L - 50 pack
C - 100 pack
D - 500 pack
M - 1,000 pack

MP **NY** - **750** - **9** **C**

Material
Nylon
TZ - Fluoropolymer
PV - PVC
PE - Polyethylene
FR - Flame Retardant
TL - Teflon

Size / #
.75"

Colour
See Colour Table

Quantity
Q - 25 pack
L - 50 pack
C - 100 pack
D - 500 pack
M - 1,000 pack

- Product Prefix**
- MP - Mounting Pad
 - ID - Identification
 - S# - Strapping Thickness
 - MC - Mounting Cradle
 - PM - Push Mounts
 - SM - Screw Mounts
 - N# - Plain-Edged Cable Clamps / Width
 - W# - Self-Aligning Cable Clamps / Dia.
 - UL - Adjustable Cable Clamps
 - GG - Gator Grip
 - FA - Flat Adhesive Clip
 - FS - Flat Screw Clip
 - FR - Flat Rubber Adhesive Clip
 - MS - Snap Mount
 - RA - Round Adhesive Clip
 - SR - Spiral Wrap
 - GS - Grommeting
 - GR - Extruded Grommeting
 - GRU - Extruded Grommeting Uncut

Colour Table	
0 - Black (Weather-Resistant)	7 - Purple
1 - Brown	8 - Grey
2 - Red	9 - Natural
3 - Orange	11 - Fluorescent Pink
4 - Yellow	16 - Fluorescent Orange
5 - Green	17 - Fluorescent Yellow
6 - Blue	18 - Fluorescent Green
	20 - Fluorescent Blue


Wire Protection Products

Extruded Grommets

Line panel edges and knockouts!

- Used to line panel edges and knockouts where the chafing of passing wires is a concern
- Available in 8 stock sizes in 100-ft. lengths for panels from 0.040 in. (1.02 mm) to 0.250 in. (6.35 mm) thick

- A variety of stocked materials to cover a wide range of applications
- Solid Wall Polyethylene is ideal for protection of glass, sheet metal, wood panels, or other sheet-form materials



Cat. No.	Material	A		B		C		D		UL Flammability	Reel Qty.					
		Max. Panel Thickness (in.)	(mm)	Grommeting Thickness (in.)	(mm)	Grommeting Height (in.)	(mm)	Grommeting Width (in.)	(mm)							
Extruded Grommets																
GRNY-040-9-C	Natural Nylon	0.04	1.02	0.04	1.02	0.19	4.83	0.13	3.18	94 V-2	1 (100 ft.)					
GRNY-052-9-C		0.05	1.32													
GRNY-062-9-C		0.06	1.57	0.05	1.32	0.20	5.08	0.17	4.32							
GRNY-085-9-C		0.09	2.16													
GRNY-100-9-C		0.10	2.54													
GRNY-125-9-C		0.13	3.18													
GRNY-187-9-C		0.19	4.75													
GRNY-250-9-C		0.25	6.35													
GRNY-040-0-C	0.04	1.02	0.04									1.02	0.19	4.83	0.13	3.18
GRNY-052-0-C	0.05	1.32														
GRNY-062-0-C	0.06	1.57		0.05	1.32	0.20	5.08	0.17	4.32							
GRNY-085-0-C	0.09	2.16														
GRNY-100-0-C	0.10	2.54														
GRNY-125-0-C	0.13	3.18														
GRNY-187-0-C	0.19	4.75														
GRNY-250-0-C	0.25	6.35														
GRPE-040-9-C	Natural Polyethylene	0.04	1.02							0.04	1.02	0.19	4.83	0.13	3.18	
GRPE-052-9-C		0.05	1.32													
GRPE-062-9-C		0.06	1.57	0.05	1.32	0.20	5.08	0.17	4.32							
GRPE-085-9-C		0.09	2.16													
GRPE-100-9-C		0.10	2.54													
GRPE-125-9-C		0.13	3.18													
GRPE-187-9-C		0.19	4.75													
GRPE-250-9-C		0.25	6.35													
GRUPE-040-9-C	0.04	1.02	0.04							1.02	0.19	4.83	0.13	3.18		
GRUPE-052-9-C	0.05	1.32														
GRUPE-062-9-C	0.06	1.57		0.05	1.32	0.20	5.08	0.17	4.32							
GRUPE-085-9-C	0.09	2.16														
GRUPE-100-9-C	0.10	2.54														
GRUPE-125-9-C	0.13	3.18														
GRUPE-187-9-C	0.19	4.75														
GRUPE-250-9-C	0.25	6.35														
GRFR-040-WH-C	Flame-Retardant White Polyethylene	0.04	1.02							0.04	1.02	0.19	4.83	0.13	3.18	
GRFR-052-WH-C		0.05	1.32													
GRFR-062-WH-C		0.06	1.57	0.05	1.32	0.20	5.08	0.17	4.32							
GRFR-085-WH-C		0.09	2.16													
GRFR-100-WH-C		0.10	2.54													
GRFR-125-WH-C		0.13	3.18													
GRFR-187-WH-C		0.19	4.75													
GRFR-250-WH-C		0.25	6.35													
GRFR-040-WH-C	0.04	1.02	0.04							1.02	0.19	4.83	0.13	3.18		
GRFR-052-WH-C	0.05	1.32														
GRFR-062-WH-C	0.06	1.57	0.05	1.32	0.20	5.08	0.17	4.32								
GRFR-085-WH-C	0.09	2.16														
GRFR-100-WH-C	0.10	2.54														
GRFR-125-WH-C	0.13	3.18														
GRFR-187-WH-C	0.19	4.75														
GRFR-250-WH-C	0.25	6.35														