30.5 mm Heavy-Duty Watertight/Oiltight—10250T

	Accessories, continued	
	Description	Catalog Number
	Hardware and Kits	
10250TK3	Thrust Washers—	10250TK3
\bigcirc	To meet Ford Motor Co. mounting specifications.	
0250TK5	Contact Block Tape Seal— Seals plunger openings on last contact block. Order in multiples of 10 pieces.	10250TK5
6-9337	Selector Switch Operator Gasket— Seals out dust from getting in-between the cam and contact block plungers.	56-9337
0	Supplied as standard with all selector switches.	
0250TA3_	Special Retaining Nut— To accommodate thick panel:	
\bigcirc	Indicating lights	10250TA30
-	PresTest, pushbuttons and selector switches	10250TA31
0250TA62	Terminal Block — Two terminals, each will accommodate two wire terminations.	10250TA62
10250TA8	Spacer Ring — Used when legend plate is not required.	10250TA8
0250TA79	Stacking Screw— Replaces transformer mounting screws on indicating light so terminal block 10250TA62 can be mounted to light to support and connect a series resistor. This screw also fits all contact blocks. Order in multiples of 10.	10250TA79
0250TA2_	Base Mounting Spacers ^① —	
Y	Equivalent to contact block in depth (one block deep).	10250TA22
	Complete with screws, washers, etc. (two block deep).	10250TA23
10250TKG_	Grounding Kits— Kits consist of a ring connector and a #6 screw for mounting connector to rear of contact block mounting screw.	
	All components except standard indicating lights and PresTest indicating lights.	10250TKG1
	Standard indicating lights	10250TKG2 2
	PresTest indicating lights	10250TKG3 ⁽²⁾
10250TA7_	Contact Block Terminal Jumpers— Available in multiples of 100 only.	
	Terminal to terminal—within block (short)	
	100 per pkg.	10250TA70
	1000 per pkg.	10250TA70-2
	Terminal to terminal—block to block (long)	
	100 per pkg.	10250TA71
	1000 per pkg.	10250TA71-2

Notes

① Component only. Not to be used for custom built (factory assembled) stations.

⁽²⁾ Not suitable for single contact block depth cast enclosure. Cover is too thick.