

Accessories

Screw Connection Terminal/Ground Blocks, Double Level

| Description | Color | Number of Positions | Standard Pack | XBUTT4 | XBUTT4PE |
|--|-------|---------------------|---------------|-------------------------------|-------------------------------|
| | | | | Catalog Number | Catalog Number |
| End cover | Gray | — | 50 | XBACUTT4 | XBACUTT4 |
| End cover segment | Gray | — | 10 | XBDPUTT4 | XBDPUTT4 |
| Partition plate | — | — | 50 | XBATUTT4 | XBATUTT4 |
| Plug-in bridge—for cross connections in the bridge shaft | Red | 2 | 10 | XBAFBS26 | XBAFBS26 |
| | | 3 | 50 | XBAFBS36 | XBAFBS36 |
| | | 5 | 50 | XBAFBS56 | XBAFBS56 |
| | | 10 | 10 | XBAFBS106 | XBAFBS106 |
| | | 50 | 10 | XBAFBS506 | XBAFBS506 |
| Test adapter | — | — | 10 | XBATSPA14 | XBATSPA14 |
| 2.3 mm diameter test plug | — | — | — | XBATSMPS- ^① | XBATSMPS- ^① |
| Modular test plug | — | — | 10 | XBATSPS6 | XBATSPS6 |
| Blank marker strip (strip of 10) | White | — | 10 | XBMZB6 ^② | XBMZB6 ^② |

Technical Data and Specifications

Screw Connection Double Level

| Description | XBUTT4 | XBUTT4PE |
|--|-------------------|-------------------|
| Technical Data in Accordance with IEC | | |
| Maximum load current in A/cross-section in mm ² | 30/6 | —/6 |
| Rated surge voltage in kV/contamination class | 8/3 | 6/3 |
| Surge voltage category/insulating material group | III/I | III/I |
| Connection Capacity | | |
| Stranded with ferrule/with ferrule and plastic sleeve in mm ² | 0.25–4/0.25–4 | 0.25–4/0.25–4 |
| Multi-Conductor Connection (same cross-section) | | |
| Solid/stranded in mm ² | 0.14–1.5/0.14–1.5 | 0.14–1.5/0.14–1.5 |
| Stranded with ferrules without plastic sleeve in mm ² | 0.25–1.5 | 0.25–1.5 |
| Stranded with twin ferrule with plastic sleeve in mm ² | 0.5–2.5 | 0.5–2.5 |
| Stripping length in inches (mm) | 0.35 (9) | 0.35 (9) |
| Thread | M3 | M3 |
| Torque in in-lb (Nm) | 5.3–7.1 (0.6–0.8) | 5.3–7.1 (0.6–0.8) |

Dimensions

Approximate Dimensions in Inches (mm)

Screw Connection Double Level

| Catalog Number | Width | Length | Cover Width | Height for— | |
|-----------------|------------|-------------|-------------|-------------|-------------|
| | | | | 35 x 7.5 in | 35 x 15 in |
| XBUTT4 | 0.24 (6.2) | 2.75 (69.9) | 0.09 (2.2) | 2.56 (65.0) | 2.85 (72.5) |
| XBUTT4PE | 0.24 (6.2) | 2.75 (69.9) | 0.09 (2.2) | 2.56 (65.0) | 2.85 (72.5) |

Notes

① For ordering information, see **Page V7-T8-103**.

② For information on Printed Marking Tag Options, see **Page V7-T8-98**.

For additional accessories, see **Page V7-T8-90**.