








System Connectivity Components

System connectivity components for the SmartWire-DT system includes cables, connectors, jumpers, bushings, plugs, sockets, flat to round cable adapters, and crimping tools.

In-Cabinet Components

	Description	Length	Pkg. Qty.	Catalog Number
Flat Cable 	Flat Cable, 8 AWG 24, 600 V			
	For SmartWire-DT network inside the control panel	328.1 ft (100 m)	1	SWD4-100LF8-24
	Complete with flat plugs SWD4-8MF2 installed at both ends	9.8 ft (3 m)	1	SWD4-3LF8-24-2S
		16.4 ft (5 m)	1	SWD4-5LF8-24-2S
		32.8 ft (10 m)	1	SWD4-10LF8-24-2S
Device Plug 	Device Plugs			
	For connection to SmartWire-DT modules or nodes	—	10	SWD4-8SF2-5
Flat Plug 	Flat Plugs			
	For connection to SmartWire-DT system components: gateways, powerfeed modules, coupling and terminating resistor	—	10	SWD4-8MF2
Device Plug Jumper 	Device Plug Jumpers			
	For bridging open, spare or inverted device plugs	—	5	SWD4-SEL8-10
PCB Jumper 	Control Station PCB Jumpers			
	For bridging open mounting locations on the control station printed circuit board	—	5	M22-SWD-SEL8-10
Universal Modules   <i>Front Mount</i> <i>Base Mount</i>	Universal (Placeholder) Modules			
	Front mount	—	20	M22-SWD-NOP
	Base mount	—	20	M22-SWD-NOPC