NEW PRODUCTS

Wire & Cable Management

OFR Series Overfloor Raceway

Page 94

Wiremold® OFR Series Overfloor Raceway System

provides four-channels of capacity and access to a wide range of power, communications, and A/V connectivity options in the smallest, lowest, narrowest, ADA compliant profile available in overfloor raceway systems.

- Lowest profile overfloor raceway available.
 Smaller, narrower, lower raceway profile reduces potential trip hazards while also being installer friendly to speed installations.
- Multiple channel base. Four-channel raceway provides space for multiple combinations of power, communication and A/V to be provided through a single raceway installation.
- Multiple options for communication and A/V connectivity. OFR Series Raceway accepts Wiremold Open System device plates that provide connectivity to a wide range of devices from leading communication and A/V providers.
- Meets ADA Accessibility Guidelines. Low profile, unobtrusive design meets the ADA Accessibility Guidelines that pertain to ADA Standard 4.5 which addresses changes in floor and ground surface levels.
- cETLus Listed.



NEW COMPONENTS:





OFR6

OFR10W





OFR15

NFR17



OFR89-VFL

880MP2 Nonmetallic Floor Boxes Page

387

Wiremold® Modulink™ 880 Series Nonmetallic Floor Boxes provide power and communication services directly to the workstation or to any open space location. The Modulink Floor Box is a gangable box that allow a one-gang floor box to easily be turned into a two-or three-gang box simply by ganging together individual boxes.

- Multiple service capability. Eliminates the cost of a separate floor box and cover to accommodate communication service.
- 2" [51mm] conduit openings. Provides the largest conduit feed in the industry. Meets customer requirements for greater communication cable capacity.
- Ratchet adjusting ring. Allows connection of cover flange without glue or mechanical fasteners. Reduces installation time and cost by providing 10° of post-pour adjustment of the cover flange.
- Conduit reducers and plugs provided. Allows direct reduction from 2" to 1/2" [51mm to 12.7mm] conduit and all sizes in between. Reduces installation time by providing direct reduction and separate plugs by eliminating the need to cut out plugs to form reducers.
- cULus Listed. Listed by Underwriters Laboratories Inc. to their standard UL514A, 514C, 514D, and Canadian standard C22.2.






OFR SERIES OVERFLOOR RACEWAY


Ordering Information

OFR89-VFL Overfloor Large Vista Transition



For connecting OFR Series Raceway to Vista Architectural Columns.

OFR11 OFR Flat Elbow




For making right angle turns on the same surface.

OFR1 OFR Coupling




Joins lengths of OFRB-8 OFR Series Raceway Base together. Sold in pairs.

OFR9 OFR Grounding Clip




Connects equipment grounding conductor to provide ground to OFR Series Raceway. No. 10 ground screw provided.

OFR47-B OFR Duplex Device Plate




For covering unused compartments in OFR48-2 and OFR48-4 Device Boxes.

OFR47-D OFR Duplex Device Plate




For covering duplex style devices in OFR48-2 and OFR48-4 Device Boxes. Accepts 106 Frame.

OFR47-R OFR Decorator Device Plate




For covering rectangular decorator style devices in OFR48-2 and OFR48-4 Device Boxes.

OFR47-UOFR Extron® MAAP-2A Device Plate




Device plate that will accept up to four (4) Extron® Electronics MAAP style plates in OFR48-2 and OFR48-4 Device Boxes.

OFR47-V OFR Extron® AAP Device Plate




Device plate that will accept two (2) Extron® Electronics AAP single space modules.

OFR47-2A OFR Communications Device Plate



Device plate that will accept up to four (4) ports of communications devices. Includes adapters for Ortronics® TracJack, Series II, Pass & Seymour® Activate inserts and Wiremold Open System communication modules.

OFR47-U2AOFR Extron® MAAP-2A Combo Device Plate



Combination device plate that will accept up to two (2) Extron® Electronics MAAP style plates and up to two (2) ports of communications devices. Includes adapters for Ortronics® TracJack, Series II, Pass & Seymour® Activate inserts and Wiremold Open System communication modules.