

CFL | Ceiling | GU24 and Occupancy Sensor | Long Twin Tube with 2G11 Base

CFL Ceiling Lampholders

Occupancy Sensor Fluorescent Ceiling Lampholders

Automatically turns light on when sensing motion.

Occupancy Sensor Fluorescent Ceiling Lampholders

| Description | Rating | Cat. No. |
|---|------------------|--------------------------|
| Lampholder with 13W Lamp Guard | 13W 120VAC, 60Hz | 9863-OCC |
| Lampholder with 13W Lamp and Lamp Guard | 13W 120VAC, 60Hz | 9863-SEN |

Note: Ceiling Mount only.

Note: Not intended for use with incandescent lamps, dimmers or occupancy sensors



9863

Long Twin Tube with 2G11 Base – Compact Fluorescent Lampholders

Features and Benefits

- Vertical snap-in model allows wires to be routed on either top or bottom of panel
- Two wiring ports per contact speed harness wiring
- Internal shunt models eliminate need for extra jumper wire in fixtures designed for electronic ballasts
- Low-profile design for smaller, more compact fixtures
- Superior metal-spring lamp retainer clips

4-Pin Long Twin-Tube with 2G11 Base – Slide-In Mounting

| Description | Rating | Cat. No. |
|--|-----------|-----------------------|
| Slide-In for 18-20 Ga. Panels, Quickwire Terminals | 660W 600V | 13452 |



13453

4-Pin Long Twin-Tube with 2G11 Base – Bottom or Back Mounting

| Description | Rating | Cat. No. |
|---|-----------|-----------------------|
| Vertical Snap-In Mounting, Side Push-In Wiring | 660W 600V | 13453 |
| Same as above, with Internal Shunt Connection for Electronic Ballasts | 660W 600V | 23453 |
| Horizontal Snap-In Mounting, Bottom Push-In Wiring | 660W 600V | 13454 |
| Same as above, with Internal Shunt Connection for Electronic Ballasts | 660W 600V | 23454 |
| Horizontal Screw-Mount, Bottom Push-In Wiring | 660W 600V | 13455 |
| Same as above, with Internal Shunt Connection for Electronic Ballasts | 660W 600V | 23455 |



13454

