## ABB contact for Canada/iew... Print to Pdf...

### **General Information**

**Extended Product Type:** IB132-G

 Product ID:
 1SAM201911R1010

 EAN:
 4013614421617

 Catalog Description:
 IB132-G Enclosure

**Long Description:** IB132-G enclosure is suitable for manual

motor starter MS116/MS132. The combination of manual motor starter and enlcosure allows to setup all required control and protection functions for single machine installations. The enclosure has a IP65 degree of protection. Additional mounting of auxiliary and signalling contacts, shunt trips and undervoltage release is possible. The handle is up to 3-

times lockable in OFF position.



# **Categories**

Products » Low Voltage Products and Systems » Control Products » Manual Motor Starters » Manual Motor Starters Accessories

# **Ordering**

**EAN:** 4013614421617

Minimum Order Quantity: 1 piece
Customs Tariff Number: 39269097

### **Container Information**

Package Level 1 Width: 129.0 mm
Package Level 1 Length: 129.0 mm
Package Level 1 Height: 141.0 mm
Package Level 1 Gross Weight: 0.435 kg
Package Level 1 Units: 1 piece

#### **Dimensions**

Product Net Width:120.0 mmProduct Net Height:120.0 mmProduct Net Depth:195.0 mmProduct Net Weight:0.370 kg

### **Technical**

Contact Position Indication:

Actuator Type:

Color:

ON / OFF / TRIP

Rotary Handle

grey/black

Degree of Protection: IP65

Standards: IEC/EN 60947-1

IEC/EN 60947-4-1

UL 508

CSA 22.2 No. 14

Product Name: Enclosure
Suitable For: MS116

MS132

Suitable for Product Class: Manual Motor Starters

**Remarks:** For detailed specification see installation instruction.

**Environmental** 

Ambient Air Temperature: Operation 0 .... +40 °C

Storage -50 ...+80 °C

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

**Technical UL/CSA** 

Enclosure Type UL/CSA: 12

**Certificates and Declarations (Document Number)** 

cUL\_E137861

**Declaration of Conformity - CE:** 1SAD938501-0188

1SAD938508-0125 1SAD938503-0183 1SAD938515-0060

GOST Certificate:1SAA937000-2703RoHS Information:1SAA963002-4405

UL\_E137861

Classifications

**E-nummer**: 3112073