

# AF65-30-00-13

[Print View..](#)  
[Print to Pdf..](#)

## General Information

<b>Extended Product Type:</b>	AF65-30-00-13
<b>Product ID:</b>	1SBL387001R1300
<b>EAN:</b>	3471523132634
<b>Catalog Description:</b>	AF65-30-00-13 100-250V50/60HZ-DC Contactor
<b>Long Description:</b>	<p>AF65 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF... contactors include an electronic coil interface accepting a wide control voltage <math>U_c</math> min. ... <math>U_c</math> max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF contactors have built-in surge protection and do not require additional surge suppressors. The AF... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, front and side-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available.</p>



## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

<b>EAN:</b>	3471523132634
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85369085

## Dimensions

<b>Product Net Width:</b>	55.0 mm
<b>Product Net Depth:</b>	111.0 mm
<b>Product Net Height:</b>	125.5 mm
<b>Product Net Weight:</b>	0.950 kg

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	150 mm
<b>Package Level 1 Length:</b>	150 mm
<b>Package Level 1 Height:</b>	87 mm
<b>Package Level 1 Gross Weight:</b>	1.05000 kg

Package Level 1 EAN: 3471523132634

---

## Environmental

---

**Ambient Air Temperature:** Close to Contactor for Storage -60...+80 °C  
Close to Contactor Fitted with Thermal O/L Relay -25 ... +60 °C  
Close to Contactor without Thermal O/L Relay -40 ... +70 °C

**Maximum Operating Altitude Permissible:** 3000 m

**Resistance to Shock acc. to IEC 60068-2-27:** Closed, Shock Direction: A 25 g  
Closed, Shock Direction: B1 25 g  
Closed, Shock Direction: B2 15 g  
Closed, Shock Direction: C1 25 g  
Closed, Shock Direction: C2 25 g  
Open, Shock Direction: B1 5 g

**Resistance to Vibrations acc. to IEC 60068-2-6:** 5...300 Hz 3 g closed position / 3 g open position

---

## Technical

---

**Rated Operational Power AC-3 ( $P_e$ ):** (220 / 230 / 240V) 18.5 kW  
(380 / 400V) 30 kW  
(415V) 37 kW  
(440V) 37 kW  
(500V) 37 kW  
(690V) 37 kW

**Rated Operational Current AC-1 ( $I_e$ ):** (690V) 40°C 105 A  
(690V) 60°C 90 A  
(690V) 70°C 80 A

**Number of Main Contacts NO:** 3

**Number of Main Contacts NC:** 0

**Number of Auxiliary Contacts NO:** 0

**Number of Auxiliary Contacts NC:** 0

**Rated Control Circuit Voltage ( $U_c$ ):** 50 Hz 100...250 V  
60 Hz 100...250 V  
DC Operation 100...250 V

**Terminal Type:** Screw Terminals

---

## Technical UL/CSA

---

**Tightening Torque UL/CSA:** Control Circuit 11 in·lb  
Main Circuit 35 in·lb

---

## Certificates and Declarations (Document Number)

---

**CB Certificate:** CB\_SE\_72130A1

**CCC Certificate:** CCC\_2012010304589737

**cUL Certificate:** UL\_20130926-E312527\_14\_1

**Declaration of Conformity - CE:** 1SBD250176C3000

**DNV Certificate:** DNV\_E12810

**EAC Certificate:** EAC\_RU C-FR ME77 B01010

**GL Certificate:** GL\_60841-13HH

**LR Certificate:** LRS\_1300087E1

**RINA Certificate:** RINA\_ELE084013XG

**RMRS Certificate:** RMRS\_1400682124

**RoHS Information:** 1SBD251021E1000

---

## Classifications

---

**E-number:** 3210045

---