



## Cable Ties




**TY523M**  
Tie body width 0.091 in.



**TY524**  
Tie body width 0.140 in.



**TY525M**  
Tie body width 0.184 in.



**TY5272M**  
Actual size body width 0.270 in.



Std. Cat. No.	Bulk Cat. No.	Type DSG	Plenum Rating	Usage	ANSI UL94 Flame Rating	Body Width (in./mm)	Length (in./mm)	Max. Wire Bundle Dia. (in./mm)	Military Standard Part No.	Tensile Strength (lb./N)	Std. Pkg.	Bulk Pkg.
<b>Ty-Rap® Standard Nylon 6/6 Cable Ties</b>												
<a href="#">TY523M</a>	<a href="#">TY23M</a>	2/21	AH-2	Indoor Only	V-2	0.09/2.29	3.62/91.95	0.87/22.00	MS3367-4	18/80.00	100	1,000
<a href="#">TY52315M</a>	<a href="#">TYB2315M</a>						7.00/177.80	1.25/32.00	–			
<a href="#">TY5232M</a>	<a href="#">TY232M</a>						8.00/203.20	2.00/51.00	–			
<a href="#">TY5234M</a>	<a href="#">TY234M</a>						14.00/355.60	4.00/102.00	–			
<a href="#">TY524M</a>	<a href="#">TY24M</a>					0.14/3.56	5.50/139.70	1.38/35.00	MS3367-5	40/180.00		
<a href="#">TY5242M</a>	<a href="#">TY242M</a>						8.19/208.03	2.00/51.00	–			
<a href="#">TY526M</a>	<a href="#">TY26M</a>						11.10/281.94	3.00/76.00	–			
<a href="#">TY5244M</a>	<a href="#">TY244M</a>						14.50/368.30	4.00/102.00	–			
<a href="#">TY525M</a>	<a href="#">TY25M</a>	2S/21S	AH-2	Indoor Only	V-2	0.19/4.83	7.31/185.67	1.89/48.00	MS3367-1	50/222.00		
<a href="#">TY5253M</a>	<a href="#">TY253M</a>						11.60/294.64	3.00/78.00	MS3367-7			
<a href="#">TY528M</a>	<a href="#">TY28M</a>						14.20/360.68	4.00/102.00	MS3367-2			
<a href="#">TY5272M</a>	<a href="#">TY272M</a>					0.27/6.86	8.75/222.25	2.00/51.00	–	120/540.00		
<a href="#">TY527M</a>	<a href="#">TY27M</a>	13.40/340.36	4.00/102.00	MS3367-3								
<a href="#">TY5275M</a>	<a href="#">TY275M</a>	18.00/457.20	5.00/127.00	–								
<a href="#">TY5277M</a>	<a href="#">TY277M</a>	24.30/617.22	7.00/177.00	–								
<a href="#">TY529M</a>	<a href="#">TY29M</a>					30.00/762.00	9.00/229.00	MS3367-6		50		
<a href="#">TY53510M**</a>	–	N/A	N/A		N/A	0.32/8.13	35.00/889.00	10.00/254.00	–	175/778.40		
<a href="#">TY54513M**</a>	–	N/A	N/A		N/A		45.00/330.20	13.00/330.20	–			

Cable ties made from natural nylon 6/6 are excellent performers in most applications. Nylon 6/6 is recommended for use in temperatures ranging from -60°C to 85°C (-76°F to 185°F). CSA Certified file 002884. Natural 6/6 Nylon Cable Ties are suitable for use in air handling plenum spaces in accordance with rules 12-010 (3), (4) and (5), and 12-020 of the CEC.

\*\* RUL  
Halogen free, Silicone free  
UL recognized models.

## Cable Ties



**TY523MX**  
Tie body width 0.091 in.



**TY524MX**  
Tie body width 0.140 in.



**TY525MX**  
Tie body width 0.184 in.



**TY5272MX**  
Actual size body width 0.270 in.

The MX Series cable ties are recommended for outdoor use.



Std. Cat. No.	Bulk Cat. No.	Type DSG	Plenum Rating	Usage	ANSI UL94 Flame Rating	Body Width (in./mm)	Length (in./mm)	Max. Wire Bundle Dia. (in./mm)	Military Standard Part No.	Tensile Strength (lb./N)	Std. Pkg.	Bulk Pkg.						
Ty-Rap® Nylon 6/6 – Weather-Resistant																		
TY523MX	TY23MX	2/21	AH-2	Indoor/ Outdoor	V-2	0.09/2.29	3.62/91.95	0.87/22.00	MS3367-4	18/80.00	100	1,000						
TY52315MX	TYB2315MX						7.00/177.80	1.25/32.00	–									
TY5232MX	TY232MX						8.00/203.20	2.00/51.00	–									
TY5234MX	TY234MX						14.00/355.60	4.00/102.00	–									
TY524MX	TY24MX					0.14/3.56	5.50/139.70	1.38/35.00	MS3367-5	40/180.00								
TY5242MX	TY242MX						8.19/208.03	2.00/51.00	–	30/130.00								
TY526MX	TY26MX						11.10/281.94	3.00/76.00	–									
TY5244MX	TY244MX					14.50/368.30	4.00/102.00	–										
TY525MX	TY25MX					2S/21S	N/A		HB	0.27/6.86			7.31/185.67	1.89/48.00	MS3367-1	120/540.00	50	500
TY5253MX	TY253MX												11.60/294.64	3.00/78.00	MS3367-7			
TY528MX	TY28MX	14.20/360.68	4.00/102.00	MS3367-2														
TY5272MX	TY272MX	8.75/222.25	2.00/51.00	–														
TY527MX	TY27MX						13.40/340.36	4.00/102.00	MS3367-3									
TY5275MX	TY275MX						18.00/457.20	5.00/127.00	–									
TY5277MX	TY277MX						24.30/617.22	7.00/177.00	–									
TY529MX	TY29MX*						30.00/762.00	9.00/229.00	MS3367-6									
TY53510MX**	–	N/A			N/A	0.32/8.13	35.00/889.00	10.00/254.00	–	175/778.40		–						
TY54513MX**	–	N/A					45.00/330.20	13.00/330.20	–									

\* For military compliance of weather-resistant black 120 lb. ties, replace suffix X with O (i.e. TY27M-O).

\*\*

Halogen free, Silicone free

CSA Certified file 002884. Natural 6/6 Nylon Cable Ties are suitable for use in air handling plenum spaces in accordance with rules 12-010 (3), (4) and (5), and 12-020 of the CEC.

Nylon 6/6 is recommended for use in temperatures ranging from -60°C to 85°C (-76°F to 185°F).