

Technical Specifications

Features

- Made from tough, resistant material which can be used without cracking at extreme cold temperatures.
- Transparent material makes installation easy and safe.
- Flange is constructed to ensure a good seal on panel surface.



BCVB-1



BCVB-2



BCVB-3



CIVB-4



BCVB-54



CI1004-VB



CI5254-VB




CI72171-VB



CIDS-55

Cat. No.	Description
Vapour Barriers — Soft Polyethylene	
BCVB-1	For 2" x 3" single device boxes up to 3" deep.
BCVB-2	For 4" square and 2 gang 2" x 3" device boxes up to 3" deep.
BCVB-3	For 3 gang 2" x 3" device boxes up to 3" deep.
CIVB-4	For 4 gang 2" x 3" device boxes up to 3" deep.
BCVB-54	For octagonal boxes up to 2-1/8" deep.

Cat. No.	Description
Vapour Barriers — High Density Polyethylene	
CI1004-VB	For 2" x 3" single device boxes up to 3" deep.
CI5254-VB	For 4" square and 2 gang 2" x 3" boxes up to 3" deep.
CI72171-VB	For 4-11/16" square boxes up to 2-1/8" deep.

Cat. No.	Description
Door Switches	
CIDS-55	3-11/16" H x 1-11/32" W x 1-1/2" deep 4.5 cu. in.
	Light's on when door's opened.
	Kit contains:
	<ul style="list-style-type: none"> • 3 Amp., 125 Volt A.C. switch with steel push button. • Steel box and mounting plate. • Mounting screws and wire connectors. • Instruction sheet.

Extension Rings/Vapour Barriers

Non-Metallic

NuTek®



WXT12



WXT18



WXT58



WSW-VB



WOCT-VB

Technical Specifications

Cat. No.	Raised
Extension Rings	
WXT-12	1/2"
WXT-18	1/8"
WXT-58	5/8"

Cat. No.	Description
Extension Rings	
WOCT-VB	Soft booth for use with WOCT ceiling boxes or 2WSW 2 gang switch boxes
WSW-VB	Soft booth for use with WSW 1 gang switch boxes