



## Flat cable, SmartWire-DT, 100m, 8-Pole

Part no.

SWD4-100LF8-24

Article no.

116026



Powering Business Worldwide™



## Delivery programme

|  |  |   |  |
|--|--|---|--|
| Product range                                  |  |   | SmartWire-DT accessories   |
| Basic function                                 |  |   | SWD ribbon cable   |
| Function                                       |  |   | For connecting the SmartWire-DT modules within the control panel |
| Description                                    |  |   | 8 pole<br>not ready-assembled                                    |
| Length   |  | m | 100  |
| Note regarding length                          |  |   | 1 off  |
| Connection to SmartWire-DT                     |  |   | yes  |
| For use with                                   |  |   | EU5C-SWD...<br>EU5E-SWD...<br>M22-SWD...<br>DIL-SWD...           |
| Protection type (IEC/EN 60529, EN50178, VBG 4) |  |   | IP20   |

## Technical data

### Ambient conditions, mechanical

|  |  |  |      |
|--|--|--|------|
| Protection type (IEC/EN 60529, EN50178, VBG 4) |  |  | IP20 |
|--|--|--|------|

### Climatic environmental conditions

|   |  |   |   |
|---|--|---|---|
| Condensation  |  |   | Take appropriate measures to prevent condensation |
| relative humidity, non-condensing (IEC/EN 60068-2-30) |  | % | 5 - 95  |

## Design verification as per IEC/EN 61439

| Technical data for design verification   |            |   |  |
|--|------------|---|--|
| Rated operational current for specified heat dissipation   | $I_n$      | A | 0  |
| Heat dissipation per pole, current-dependent   | $P_{vid}$  | W | 0  |
| Equipment heat dissipation, current-dependent  | $P_{vid}$  | W | 0  |
| Static heat dissipation, non-current-dependent   | $P_{vs}$   | W | 0  |
| Heat dissipation capacity  | $P_{diss}$ | W | 0  |
| IEC/EN 61439 design verification   |            |   |  |
| 10.2 Strength of materials and parts   |            |   |  |
| 10.2.2 Corrosion resistance  |            |   | Meets the product standard's requirements.   |
| 10.2.3 Verification of thermal stability of enclosures   |            |   |  |
| 10.2.3.1 Verification of thermal stability of enclosures   |            |   | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |            |   | Meets the product standard's requirements.   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |            |   | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |            |   | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |            |   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |            |   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |            |   | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES  |            |   | Meets the product standard's requirements.   |
| 10.4 Clearances and creepage distances   |            |   | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |            |   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components   |            |   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections  |            |   | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |            |   | Is the panel builder's responsibility.   |
| 10.9 Insulation properties   |            |   |  |
| 10.9.2 Power-frequency electric strength   |            |   | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |            |   | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material   |            |   | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |            |   | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |

|                                     |  |  |
|-------------------------------------|--|--|
| 10.11 Short-circuit rating          |  | Is the panel builder's responsibility.   |
| 10.12 Electromagnetic compatibility |  | Is the panel builder's responsibility.   |
| 10.13 Mechanical function           |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 6.0

|  |                 |                                 |
|--|-----------------|---------------------------------|
| Cables and wires unpreassembled (EG000001) / Data cable (EC000830)   |                 |                                 |
| Electric engineering, automation, process control engineering / Cable, wire / Communication cable / Data cable (ecl@ss8.1-27-06-18-01 [AKE197011]) |                 |                                 |
| Conductor material   |                 | Cu, tinned                      |
| Diameter conductor   | mm              | 1.35                            |
| Nominal cross section conductor  | mm <sup>2</sup> | 0.23                            |
| AWG-size   |                 | 24                              |
| Conductor category   |                 | Class 2 = stranded              |
| Number of cores  |                 | 8                               |
| Stranding element  |                 | No                              |
| Core insulation  |                 | PVC                             |
| Core identification  |                 | Colour                          |
| Screen over stranding element  |                 | None                            |
| Screen over stranding  |                 | None                            |
| Material outer sheath  |                 | PVC                             |
| Colour outer sheath  |                 | Green                           |
| Halogen free (acc. EN 60754-1/2)   |                 | Ja                              |
| Flame retardant  |                 | In accordance with EN 60332-1-2 |
| Low smoke (acc. EN 61034-2)  |                 | No                              |
| Outer diameter approx.   | mm              | 17.5                            |
| Permitted cable outer temperature, in movement   | °C              | -10 - 105                       |
| Permitted cable outer temperature, fixed   | °C              | -30 - 105                       |
| Category   |                 | -                               |
| NVP value  |                 | 66.7                            |

## Approvals

|                                      |  |                          |
|--------------------------------------|--|--------------------------|
| UL File No.                          |  | E29184                   |
| UL Category Control No.              |  | NKCR                     |
| CSA File No.                         |  | 2324643                  |
| CSA Class No.                        |  | 3211-07                  |
| North America Certification          |  | UL listed, CSA certified |
| Specially designed for North America |  | No                       |

## Additional product information (links)

|   |   |
|---|---|
| <b>IL04716001Z (AWA1160-2512) SmartWire-DT: Wiring material and accessories</b> |   |
| IL04716001Z (AWA1160-2512) SmartWire-DT: Wiring material and accessories        | <a href="ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716001Z2014_10.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716001Z2014_10.pdf</a> |
| IL04716001Z (AWA1160-2512) SmartWire-DT: Wiring material and accessories        | <a href="ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716001Z2015_08.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716001Z2015_08.pdf</a> |
| <b>MN05006002Z (AWB2723-1617) SmartWire-DT, The system</b>                      |   |
| MN05006002Z (AWB2723-1617) SmartWire-DT, Das System - Deutsch                   | <a href="ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05006002Z_DE.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05006002Z_DE.pdf</a>                   |
| MN05006002Z (AWB2723-1617) SmartWire-DT, The system - English                   | <a href="ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05006002Z_EN.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05006002Z_EN.pdf</a>                   |
| MN05006002Z (AWB2723-1617) SmartWire-DT, il sistema - italiano                  | <a href="ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05006002Z_IT.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN05006002Z_IT.pdf</a>                   |