
Thomas&Betts





Ring Terminal T&B Catalog Number:

UPC Number: Status: Description: C71 78621081079 Active

Non-Insulated Ring Terminal For Wire Range 12-10 Stud Size 1/4, Metal-

lic WEB_USE

WEB_USE	
US Cutsheet PDF Catalog Link	http://www-public.tnb.com/contractor/docs/ stakon.pdf
Features	
	These non-insulated ring terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single in- dentor or double indentor (recommended for solid wire). Serrated barrel increases grip on wire.
General	
Insulation Type	Non-Insulated
Terminal Series	C
Material	Copper
Finish	Electro -Tin Plated
Color	Metallic
Wire Range	12-10
Stud Size	1/4
Dimension Information	1/-
Stock Thickness	.04
A (inches)	.91
B (inches)	.50
C (inches)	.27
M (inches)	.66
Specifications	
Temperature Rating	150°C
Voltage Rating	600V
Flammability Rating	UL 94 V-0
Tooling	
T 101 1	
Tool Charts	Available on Website
Application Tools	WT110M, WT111M, WT112M, WT2000, ERG4002
Recommended Tool	ERG4002, ERG4005
Packaging	
T&B Order Multiple	500
T&B Inner Pack	500
Package in Units	5000
Package Type	Bulk
T&B Sold in UOM	Each
T&B Weight Per UOM	4.38 lbs. per 1000
Alternate Package Qty	C10-14
Application Support	
Overview	Available on Website
Wire Guide Tables	Available on Website



Notes

Most terminals can be put on Mylar Tape for reel fed applications by adding the suffix M to the bulk catalog numbers.

Certifications

RoHS Compliance



File Nbr: E9809

For further technical assistance, please contact us...

Yes

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com