

Metal Clad Cable Termination Fittings & Accessories T&B Catalog Number:

ST400-486

UPC Number: 78621087764 Active

Status: Description:

Star Teck aluminum jacketed cable fitting, hub size-4 in.	
Features	
Easy Installation-Exclusive pow grip that's high up on the cable- volution-so strip length and cutt critical.	not on the first con-
Dependable Service-stainless s Withstands corrosive environm Dependable Grounding-Power- ring is non-magnetic stainless s 360° long-term dependal makes immediate contact with Watertight-Tapered bushing. C vide a secure, tight fit while elin	ents. Non-magnetic. Grip grounding steel. Provides ble grounding. It the cable. one shaped to pro-
water in vertical installations.	illiating cupping of
Easy to Install In Tight Spaces- fits tight spaces. Has grooves fi lation, and flats for a wrench. D with funnel entry for easy cable	or screwdriver instal- urable and reusable
Application	
Provides means for passing an jacketed cable through a bulkh	ead or enclosure
in hazardous areas. (these fittir hazardous areas when used wi pound).	-
hazardous areas when used wi	th T&B sealing com-
hazardous areas when used wi pound). Form a mechanical grip and wa	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used wi pound). Form a mechanical grip and wa tant termination.	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used windown pound). Form a mechanical grip and water termination. Provide grounding continuity of	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wate tant termination. Provide grounding continuity of General	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information Hub Size (inches) 4	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900 Dimension B (inches) 4.840	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900 Dimension B (inches) 4.840 Dimension C (inches) 6.435	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of general Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900 Dimension B (inches) 4.840 Dimension C (inches) 6.435 Range Over Jacket -Minimum (inches) 4.120	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900 Dimension B (inches) 4.840 Dimension C (inches) 6.435 Range Over Jacket -Minimum (inches) 4.120	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900 Dimension B (inches) 4.840 Dimension C (inches) 6.435 Range Over Jacket -Minimum (inches) 4.120 Range Over Jacket -Maximum (inches) 4.340	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900 Dimension B (inches) 4.840 Dimension C (inches) 6.435 Range Over Jacket -Minimum (inches) 4.120 Range Over Jacket -Maximum (inches) 4.340 Range Over Armor -Minimum (inches) 3.910	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of general Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900 Dimension B (inches) 4.840 Dimension C (inches) 6.435 Range Over Jacket -Minimum (inches) 4.120 Range Over Jacket -Maximum (inches) 4.340 Range Over Armor -Minimum (inches) 3.910 Range Over Armor -Maximum (inches) 4.220	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900 Dimension B (inches) 4.840 Dimension C (inches) 6.435 Range Over Jacket -Maximum (inches) 4.120 Range Over Jacket -Maximum (inches) 4.340 Range Over Armor -Minimum (inches) 3.910 Range Over Armor -Maximum (inches) 4.220 Specifications	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900 Dimension B (inches) 4.840 Dimension C (inches) 6.435 Range Over Jacket -Minimum (inches) 4.120 Range Over Jacket -Maximum (inches) 4.340 Range Over Armor -Minimum (inches) 3.910 Range Over Armor -Maximum (inches) 4.220 Specifications 3dmodel Available on Website	th T&B sealing com- ater and/or oil-resis-
hazardous areas when used with pound). Form a mechanical grip and wastant termination. Provide grounding continuity of General Material Aluminum Dimension Information Hub Size (inches) 4 Dimension A (inches) 3.900 Dimension B (inches) 4.840 Dimension C (inches) 6.435 Range Over Jacket -Minimum (inches) 4.120 Range Over Jacket -Maximum (inches) 4.340 Range Over Armor -Minimum (inches) 3.910 Range Over Armor -Maximum (inches) 4.220 Specifications 3dmodel Available on Website	th T&B sealing com- ater and/or oil-resis-



Application Support

T&B Instruction Sheets ta00904-tb2

Product Specifications & Overview Available on Website

Certifications

RoHS Compliance Yes

Certifications



File Nbr: E 38947

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

 ${\bf Email: tech support@tnb.com}$

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com