Technical Information Bulletin





Diameter

Date:	Name of distributor:	
In hands date of project:	Client #:	
Project name/Number:	Name of end user:	

ORDERING INFORMATION

66293 Order code:

Description: P30S/12W/30K/25/CHOICE/STD

UPC: 69549662933

Case quantity: 6



MOL: 3 3/8 in. (85mm)

Dia.: 3 3/4 in. (95 mm)

PERFORMANCE DATA

Shape: PAR30SN Base: E26 Watts(W): 12 Volts (VAC): 120 Colour temperature (K)**: 3 000 15 000 Life L70 (hrs): Initial lumens (lm)*: 965 Initial lumens per watt (lm/W): 80 CRI: 92 Beam angle (°): 25 CBCP: 3 843 0.93 Power factor:

-20 °C to 40 °C (-4 °F to 104 °F) Operating temperature range:

Traditional equivalent (W): 75

*Initial lumens range: +/- 10 %

**Typical colour temperature range: +/- 10 %

















COMPATIBLE DIMMERS

Legrand	HCL453P, RH703PTUTC
Cooper	AAL06, DAL06P, SLC03P
Leviton	6615, 6674, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ, IPL06
Lutron	AYCL-253P, CTCL-153P, DVCL-153P, DVCL-253P, DVELV-300P, MACL-153P, PD-6WCL, SELV-300P

CAUTIONS

- Turn power off before inspection, installation, or removal.
- · Risk of electrical shock do not use where directly exposed to water or weather.
- · Not for use in totally enclosed luminaires.
- · Suitable for use in wet locations.

- Do not open no user serviceable parts inside.
 Use only on 120 VAC, 60Hz circuits.
 This device is not intended for use with emergency exit fixtures or emergency exit lights.
- · Compatible with most dimmers.
- For complete dimmer and warranty information visit www.standardpro.com.

Qty	Description	Price	
I accept the sp	ecifications of the luminaire configuration	mentioned above.	
Name:			
Company:			
Signature:		Date:	

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications. Data is based upon tests performed in a controlled environment and representative of relative performance.

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.