

## S39394

54W/LED/HID/5000K/100-277V/EX39 54 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 100V 277V
  UL approved for totally enclosed fixtures
  Damp location IP64 rated

- For outdoor & indoor use
- High-bay / Low-bay / Post-top
  Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

## Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
  Working Voltage AC90-305V

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size							
Length	Width	Depth					
8 inch	8 inch	15.75 inch					

**Optional Accessories** 

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406

Item Number	Product Line	UPC	Input Voltage	Watts	Operating Frequency	Incandescent Equivalent	Fluorescent Equivalent
S39394	Hi-Pro	045923303944	100 - 277	54	50/60Hz	300W	85W



S39394

HID Equivalent	Base	ANSI Base	Lamp Code					Di	Dimmable/Non- Dimmable			inish	MOL In Inches	MOD In Inches	
250W	Mogul Extended	EX39	54W/LED/HID/5000 277V/EX39				0-	Non-Dimmable			V	White	9-1/32"	3-11/32"	
Initial Lumens	Average Rat	ed	Kelvin Temp		Color	CRI	Bea	m Spr Deg	ead	Op	oeratir	ng Tem	perature		Pack
7722	50000		5000	Na	tural Light	80	_	300		-20C	C (-4F) to a maximum o +65C (+149F)				12
Package Type	CEC Status	[	DLC ID:		Material		RoHS Compli			. or Listed	UL C	Classific	cation	Warı	ranty
Box	Lawful for sale in California	LXDJH DLC S	IRLRK97 earch		Aluminun	n	Yes		Y	es		us - Da		<u>5 Y</u> Lim	<u>ear</u> <u>nited</u>



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051