

TPS3 12

Type 1 Surge Protective Device (SPD) For Line Side or Load Side Applications

Features:

- UL 1449 3rd Edition – 2009, cUL
- Type 1 SPD (Type 2 cUL)
- Mounts external to electrical distribution equipment
 - Recommended for line side or load side applications
- Large block, individually fused, thermally protected, 50kA MOV's
- 20kA I_n (most models)
- 200kA SCCR (most models)
- Provides replaceable module protection for low to high exposure applications
- All UL-required OCP & safety coordination included
- UL96A Lightning Protection Master Label compliant (@20kA In)

■ SPD Specifications

- Surge Current Rating Per Phase

Per Phase	L-N	L-G	N-G
100kA	50kA	50kA	50kA
150kA	100kA	50kA	50kA
200kA	100kA	100kA	100kA
250kA	150kA	100kA	100kA
300kA	150kA	150kA	150kA
400kA	200kA	200kA	200kA
500kA	250kA	250kA	250kA

- 100% monitoring – Every MOV is monitored, incl. N-G
- Individually fused and thermally protected MOV's
- Solid state bi-directional operation
- EMI/RFI filtering: Active tracking up to -50db from 10kHz to 100MHz
- Repetitive impulse: 5,000 hits
- Less than 1 nanosecond response time
- Relative humidity range: 0 -95% non-condensing
- Operating frequency: 47-63Hz
- Operating temperature: -25°C (-15°F) to +60°C (140°F)

■ Standard Configuration

- Standard NEMA 1/12/3R/04 ANSI 61 steel enclosure
- Wire size: #8 AWG to 1/0
- Standard size: 12" x 12" x 7" (305mm x 305mm x 178mm) *
- Standard weight: 20 lbs. (9.07 kg) *

*Internal disconnect options and other NEMA ratings may increase enclosure size and weight



UL 1449 3rd Edition SPD

SIEMENS

- SPD Features
 - UL 1449 3rd Edition effective September 2009
 - Designed, manufactured and tested consistent with:
 - ANSI/IEEE C62.41.1-2002, c62.41.2-2002, C62.45-2002,
 - 1992/2000 NEMA LS-1
 - NEC Article 285
 - IEC 61643, CE
 - Large block, individually fused, thermally protected, 50kA MOV's
 - 10 year warranty

- SPD Monitoring
 - LED indicators
 - Audible alarm with silence switch and test button
 - Dry contacts
- Available Options
 - Surge counter
 - Internal rotary disconnect switch
 - Thru-door disconnect switch
 - NEMA 4X non-metallic enclosure
 - NEMA 4X stainless steel enclosure
 - Flush mount enclosure
 - NEMA 1 Enclosure with extended display*
 - *For line side mounting in SWBD/SWGR

- Key Bid Specifications
 - UL 1449 3rd Edition – 2009, cUL
 - Type 1 SPD
 - Protection modes on L-N, L-G, L-L, N-G
 - I_n Rating – 20kA
 - Short Circuit Current Rating – 200kA
 - Surge Current Rating
 - Per Phase = L-N + L-G
 - 100kA 50kA 50kA

Ordering Information

Catalog #



Voltage Code	Surge Current (kA)	Enclosure	Options
A = 120/240V, 1Ø, 3W (Fig 1)	10 = 100kA per phase	0 = Standard NEMA 1/12/3R/4 Steel	D = Internal rotary disconnect
B = 120/240V, 3Ø, 4W (Fig 3)	15 = 150kA per phase	V = NEMA 4X non-metallic	T = Thru-door disconnect
C = 120/208V, 3Ø, 4W (Fig 2)	20 = 200kA per phase	S = NEMA 4X stainless steel	X = Surge counter
D = 240V, 3Ø, 3W (Fig 4)*	25 = 250kA per phase	F = NEMA 1 flush mount	
E = 277/480V, 3Ø, 4W (Fig 2)	30 = 300kA per phase	P = NEMA 1 screwcover pullbox with extended display on 6ft cable for line side mounting in SWBD/SWGR	
F = 480V, 3Ø, 3W (Fig 4)*	40 = 400kA per phase		
G = 600V, 3Ø, 3W (Fig 4)**	50 = 500kA per phase		
K = 380/220V, 3Ø, 4W (Fig 2)			
L = 600/347V, 3Ø, 4W (Fig 2)			
S = 400/230V, 3Ø, 4W (Fig 2)			

- Example: TPS3C12100XD = Type 1 SPD for a 208/120V application with a surge current capacity of 100kA per phase, in a standard NEMA 1/12/3R/4 enclosure with a surge counter and internal rotary disconnect option
- *Not available in 500kA
- **Available in 100kA, 150kA, 200kA & 250kA only
- When an option is not selected, include a zero (0) in the field

Available accessories: Must be ordered separately

- RMSIE = Remote monitor

UL 1449 3rd Edition - 2009 Test Data Summary
Voltage Protection Rating (VPR - 6kV, 3kA)

Voltage Code	Service Voltage	L-N	L-G	N-G	L-L	Type*	I _n	SCCR	MCOV
A	120/240V, 1Ø, 3W (Fig 1)	700	700	700	1200	Type 1	20kA	100kA	150
B	120/240V, 3Ø, 4W (Fig 3)	700 / 1200	700 / 1200	700	1800/1800	Type 1	20kA	200kA	150 / 320
C	120/208V, 3Ø, 4W (Fig 2)	700	700	700	1200	Type 1	20kA	200kA	150
D	240V, 3Ø, 3W (Fig 4)		1200		1200	Type 1	20kA	200kA	320
E	277/480V, 3Ø, 4W (Fig 2)	1200	1200	1200	2000	Type 1	20kA	200kA	320
F	480V, 3Ø, 3W (Fig 4)		1800		1800	Type 1	10kA	200kA	552
G	600V, 3Ø, 3W (Fig 4)		2500		2500	Type 1	10kA	200kA	690
K	380/220V, 3Ø, 4W (Fig 2)	1200	1200	1200	2000	Type 1	20kA	200kA	320
L	600/347V, 3Ø, 4W (Fig 2)	1500	1500	1500	2500	Type 1	10kA	200kA	420
S	400/230V, 3Ø, 4W (Fig 2)	1200	1200	1200	2000	Type 1	20kA	200kA	320

- VPR may increase when disconnect switch is added
- VPR may decrease for products 400 & 500kA per phase

* Type 2 cUL




Figure 1
Split
2 Hots, 1 Neu, 1 Grnd




Figure 2
Wye
3 Hots, 1 Neu, 1 Grnd




Figure 3
Hi-Leg Delta (B High)
3 Hots, (B High),
1 Neu, 1 Grnd




Figure 4
Delta & HRG Wye
3 Hots, 1 Grnd

Siemens Industry, Inc.
Building Technologies Division
5400 Triangle Parkway
Norcross, GA 30092

1-800-964-4114
info.us@siemens.com

©2009 Siemens Industry, Inc.
All Rights Reserved. Siemens is a registered trademark of Siemens AG. Product names mentioned may be trademarks or registered trademarks of their respective companies. Specifications are subject to change without notice.

RPFL-IADT1-0809 (New)

www.usa.siemens.com/spd