Technical Information Bulletin



FLUO LED _

Date:	Name of distributor:	
In hands date of project:	Client #:	
Project name/Number:	Name of end user:	

1.3" (32.20 mm) I

ORDERING INFORMATION

Order code: 67259

UCFL/60IN/120V/25W/30K/FR/WH/STD **Description:**

UPC: 69549672598

Case quantity:

PHYSICAL DATA

FLUO LED Type: Length in (mm): 60 (1524) Shape: Linear **Housing Material:** Aluminum Finish: White Lens Finish: Frosted Mounting: Surface

Daisy chain installation: 12 units (300 W) can be installed in row

PERFORMANCE DATA

TECHNICAL DRAWINGS AND DIMENSIONS

60"(1524 mm)

Watts (W): 25 Volts (VAC): 120 Colour temp. (K)2: 3 000 Lumen output (lm)1: 2 000 Lumen per Watts (lm/W): 80 CRI: 90 Life L70 (h)3: 50 000 120 Beam angle (°): THD (%): < 0.15

Power factor: 0.95 Dimming: Forward AND Reverse -20°C to 40°C (-4°F to 104°F)

³Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations



Qty













COMPATIBLE ACCESSORIES

Order code	Description	Туре					
67787	UC/HARDWIREBOX/120V/STD	Hardwire Box					
67202	UCS/PLUG/120V/STD	120 V Power Cord Plug					
67203	UCS/JUMPER/6IN/STD	6" Jumper					
67204	UCS/JUMPER/24IN/STD	24" Jumper					
67205	UCS/JUMPER/36IN/STD	36" Jumper					

COMPATIBLE DIMMERS

Price

Brand	Model
LEGRAND	PD-5NE, RH703PTUTC
LUTRON	PD-6WCL, DVCL-153P, CTCL-153P, DVCL- 253P, AYCL-253P, DVRP-253P-WH, SELV-300P, MACL-153P
COOPER	RRD-6NA-WH, SCL03P
LEVITON	6615, IPL06, 6674, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ, DDMX1

DESCRIPTION AND OTHER OPTIONS

UCFL	/	ϵ	OIN	/	120V	/	2	5W	/		30K	'	FR	/		WH	/		STD
Family		L	ength		Voltage (VAC)		Wa	ttage		Colour T	emperature (K)	Le	ns Finish		Housin	ng Colour Finish			Brand
UCFL Undercabinet FLUO LED		12IN 24IN 36IN 48IN 60IN	12 inches 24 inches 36 inches 48 inches 60 inches		120V 120 Volts		5W 10W 15W 20W 25W	5 Watts 10 Watts 15 Watts 20 Watts 25 Watts		30K 40K	3 000 K 4 000 K	FR	Frosted		WH	White		STD	STANDARD

I accept the spe	ecifications of the luminaire configuration mentioned above.		
Name:			
Company:			
Signature:		Date:	

Description

Operating temp. range:

¹ Initial lumens range: +/- 5% ² Typical colour temperature range: +/- 5 %