OFF time and repeating)

Catalog Number Selection

All configurations from Catalog Number Selection are available. <u>TMR5 N 05 120</u> **Family Type** Input Voltage TMR5 120 = 120 Vac/Vdc **24** = 24 Vac/Vdc 12 = 12 Vac/Vdc **Operational Mode** 240 = 240 Vac/Vdc 8-Pin Octal Sockets 11-Pin Octal Sockets N = ON delay = OFF delay, control switch trigger Timing Range ② T = Interval ON C = Single shot, control switch trigger **04** = 0.05–5 sec L = Flasher-pause-first W = Watchdog, control switch trigger **05** = 0.1–10 sec R = Repeat cycle 1 (retriggerable single shot) **08** = 0.6–60 sec (OFF time first followed by **P** = OFF delay, power trigger **12** = 3-300 sec ON time and repeating) = Single shot, power trigger **15** = 0.3–30 min **16** = 0.6–60 min Repeat cycle ① **D** = Watchdog, power trigger (retriggerable single shot) (ON time first followed by

Product Selection

TMR5 Time Delay Relays

Input Voltage	Socket	Timing Range	Catalog Number
ON Delay			
120 Vac/Vdc	8-pin	0.1-10 sec	TMR5N05120
		0.6-60 sec	TMR5N08120
24 Vac/Vdc		0.1-10 sec	TMR5N0524
		0.6-60 sec	TMR5N0824
OFF Delay, Co	ontrol Switch T	rigger	
120 Vac/Vdc	11-pin	0.1-10 sec	TMR5F05120
		0.6-60 sec	TMR5F08120
24 Vac/Vdc		0.1-10 sec	TMR5F0524
		0.6-60 sec	TMR5F0824
Interval ON			
120 Vac/Vdc	8-pin	0.1-10 sec	TMR5T05120
		0.6-60 sec	TMR5T08120
24 Vac/Vdc		0.1-10 sec	TMR5T0524
		0.6-60 sec	TMR5T0824
Single Shot,	Control Switch	Trigger	
120 Vac/Vdc	11-pin	0.1-10 sec	TMR5C05120
		0.6-60 sec	TMR5C08120
24 Vac/Vdc		0.1-10 sec	TMR5C0524
		0.6-60 sec	TMR5C0824
Repeat Cycle (OFF Time Fir	st Followed by	ON Time and Repe	eating)
120 Vac/Vdc	8-pin	0.1-10 sec	TMR5R05120
		0.6-60 sec	TMR5R08120
24 Vac/Vdc		0.1-10 sec	TMR5R0524
		0.6-60 sec	TMR5R0824
Repeat Cycle (ON Time Firs	st Followed by	OFF Time and Repe	eating)
120 Vac/Vdc	8-pin	0.1-10 sec	TMR5Y05120
		0.6-60 sec	TMR5Y08120
24 Vac/Vdc		0.1-10 sec	TMR5Y0524
		-	

0.6-60 sec

TMR5Y0824

Accessories

Accessories for Use with TMR5 Time Delay Relays

22 = 6 sec-10 min

Description	Standard Pack	Number
8-pin socket	10	D3PA2
11-pin socket	10	D3PA3-A2
Hold-down spring	10	D65CHDS

Notes

- ① Indicates DUAL knob unit. All dual knob units can have independently selectable and adjustable ON and OFF times. If different ON and OFF times are desired, add two codes for time ranges in the part number. The first code listed indicates the first timing range of the unit (OFF time for R, ON time for Y) and the second code indicates the second timing range (ON time for R, OFF Time for Y).
- ② Fixed time delay settings are available for orders of 50 pieces or more. Contact EatonCare for additional information at 877-ETN-CARE (386-2273).