

A

B

C

D

E

F


G























H

I

X

Contact blocks

		Cat. no.	Ref. no.
<p>Logic Reed</p> <p>A new range of LOGIC REED contact blocks with faston terminals for use with power lower than 12V - 5mA.</p> 	Contact type	NC	P9B01FH 187014
		NO	P9B10FH 187015
	Rated voltage	AC2 to 120V max. DC2 to 30V max.	
	Rated current	AC/DC - 0.001 to 0.15A max.	
	Rated power	AC - 8VA max. DC - 4.5W max.	
	Minimum centerline distance	30x32 mm.	
	Mounting on operators	through specific bayonet flange adaptor.	P9ACFSM 187846
	Full voltage power supply		P9PDHF 187056

	With screw	Contact type	Cat. no.	Ref. no.
	 <p>min. 1 of 22 AWG (0.32 mm²) max. 2 of 12 AWG (3.3 mm²)</p>			
	 	NC+NO	P9B11VN	187000
	 	NC+NC	P9B02VN	187008
		NO+NO	P9B20VN	187009
	 	NC	P9B01VN	187001
		NO	P9B10VN	187002
	 	NC late opening	P9B01VR	187003
		NO early closing	P9B10VA	187004
	<p>Faston</p>  <p>1 x (6.35 x 0.8 mm) 2 x (2.8 x 0.8 mm)</p>  	NC	P9B01FN	187012
		NO	P9B10FN	187013
	<p>Terminal adapter printed circuit board adapter</p>		P9ACA6	188804

The catalogue numbers in **bold** are available from stock.