



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Number of rack unit	1U
Number of cables	1
Communication port protocol	HTTP HTTPS SNMP
Provided equipment	Country-specific detachable power cord Installation guide Rack mounting brackets Temperature/Humidity sensor
Product compatibility	Rack sensor pod 150

General

Connections supported	Alarm beacon 1 Modbus Output (RS-485) 1 Relay output 1
Universal sensor supported	Door contact Dry contact Humidity Smoke Fluid spot leak Temperature Vibration
Number of universal sensor ports	6
Number of sensor pods supported	0
Number of universal sensors supported	6
Sensor humidity	11...89 % +/- 3 % RH
Number of supported camera	0 integrated 0 networked 0 USB
Measurement range	15...50 °C +/- 1 °C 32...122 °F +/- 1.8 °F

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Physical

Height	4.4 Cm
Width	43.2 Cm
Depth	5.9 Cm
Net weight	1.27 Kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Not rack-mountable
Mounting position	Vertical

Environmental

Ambient air temperature for operation	0...45 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-15...65 °C
Storage altitude	0.00...15240.00 M
Storage Relative Humidity	0...95 %

Communications & Management

Communication network type	RJ45 10/100 Base-T
----------------------------	--------------------

Packing Units

Package 1 Weight	2.95 Kg
Package 1 Height	6.6 Cm
Package 1 width	45.7 Cm
Package 1 Length	22.6 Cm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	--

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **Commercialised**